





	MOUNTING PLATE BM-130X280/ECO	RJ-45 PLUG INTERNAL SHIELD RJ45/WP-P/INF	INDUSTRIAL POE SWITCH TSW200 8-PORT SFP Teltonika	MULTIMEDIA OUTLET GMDF-352
				
	15.08 USD 15.08 USD	0.07 USD 0.07 USD	79.25 USD 79.25 USD	16.76 USD 16.76 USD
Mount	Surface-mounted
Application	...	RJ-45 modular plug internal shield
Sockets type	• 1 pcs DATA, • 2 pcs RTV
Pole diameters range	Ø 43 mm ... Ø 200 mm
TV frequency range	87 ... 1000 MHz
Material	Steel - powder painting	Rubber
Color	White	Violet
Radio frequency range	87 ... 1000 MHz
LAN ports	• 8 RJ45 (8 x PoE+ (802.3af/at)), • 2 x SFP (Uplink)	...
Frequency range for DATA line	5 ... 65 MHz
Management	—	...
TV tap attenuation	87 ... 862 MHz @ 7.5 max. 8.5 dB 862 ... 1000 MHz @ 8.5 max. 9.5 dB
Transmission speed	• 10 / 100 / 1000 Mbps - 8 LAN & PoE ports, • 1000 Mbps - 2 SFP (Uplink) ports	...
LED diodes	Power, Link/Act, SFP	...
Maximal output power	30 W / port PoE - 1 ... 8 ports	...
Radio tap attenuation	87 ... 862 MHz @ 7.5 max. 8.5 dB 862 ... 1000 MHz @ 8.5 max. 9.5 dB
Maximal total power	240 W	...
MAC addresses table	2k	...
DATA tap attenuation	5 ... 65 MHz @ 9.5 max. 10.5 dB

Main features	<ul style="list-style-type: none"> • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Durable aluminum housing • Shock-proof • Industrial wide temperature design. • Mounting on DIN rail, • 2-pin industrial power socket, • Wide range of supported supply voltages • Grounding • "Index of Protection" : IP30 	<ul style="list-style-type: none"> • Full, double galvanic isolation between input and outputs • High voltage input protection 2.12 kV / DC • Protection system against core inverse magnetization due to high level signals • Solid, die-cast metal housing
Certificates	CE, UKCA, FCC	...
Housing	Aluminum	...
Power supply	<ul style="list-style-type: none"> • 7 ... 57 V DC (power adapter not included), • 44 ... 57 V DC - PoE IN 	...
Power consumption	<ul style="list-style-type: none"> • max. 5.5 W • PoE max. 245.5 W 	...
Operation temp	-40 °C ... 75 °C	...
Weight	0.71 kg	0.001 kg	0.51 kg	0.12 kg
Dimensions	276 x 134 x 34 mm	27 x 12 x 15 mm	132 x 44 x 95 mm	98 x 80 x 27 mm
Manufacturer / Brand	Teltonika	TELMOR
Guarantee	2 years	2 years	2 years	2 years