




	<a href="#">SWITCHING ADAPTER 24V/0.41A-TP-V2 MW POWER</a>	<a href="#">CABLE MANAGER TRSH-8- R*P10</a>	<a href="#">AHD, HD-CVI, HD-TVI CAMERA APTI-H50V3-2812 2Mpx / 5Mpx 2.8 ... 12 mm</a>
			
	14.93 PLN 14.93 PLN	5.60 PLN 5.60 PLN	190.40 PLN 190.40 PLN
Adapter type	Switching	...	...
Power voltage	100 ... 240 V AC	...	...
Standard	...	...	AHD, HD-CVI, HD-TVI
In package	...	<b>10 pcs The price for package</b>	...
Sensor	...	...	1/2.7 " CMOS
Hole diameter	...	Ø 8 mm	...
Frequency range	50 / 60 Hz	...	...
Matrix size	...	...	5 Mpx
Assembly	...	The bottom layer is equipped with a Scotch tape	...
Output voltage	24 V DC	...	...
Output voltage tolerance	± 0.5 V	...	...
Material	...	Plastic	...
Maximal load	0.41 A	...	...
Output power	10 W	...	...
Number of outputs	1 pcs	...	...
Main features	Can be installed in a 60mm electrical box	...	...
Housing type	Plastic	...	...
Operation temp	-20 °C ... 50 °C	...	...
Resolution	...	...	2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps, 12.5 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25 fps, 30 fps , 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI
Range of IR illumination	...	...	30 m
IR illuminator power adjustment	...	...	Automatic
Lens	...	...	2.8 ... 12 mm
View angle	...	...	<ul style="list-style-type: none"> <li>• 88 ° ... 31 ° (manufacturer data)</li> <li>• 93 ° ... 35 ° (our tests result)</li> </ul>

Video output	...	...	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - Via OSD, selectable by switch
Main features	...	...	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• DNR - Digital Noise Reduction</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Auto White Balance</li> <li>• Day/Night mode - configurable</li> <li>• Sharpness - sharper image outlines</li> </ul>
OSD menu	...	...	✓
Vandal-proof	...	...	—
"Index of Protection"	IP67	...	IP66
Power supply	...	...	12 V DC / 400 mA
Power consumption	...	...	≤ 4.8 W
Housing	...	...	Dome - Metal
Color	...	Red	Graphite
Operation temp	...	...	-20 °C ... 60 °C
Weight	0.07 kg	...	0.55 kg
Dimensions	Ø 50 x 23 mm	...	Ø 120 x 100 mm
Supported languages	...	...	Polish, English, French, Spanish, Portuguese, Russian, Italian
Manufacturer / Brand	MW POWER	...	APTI
Guarantee	2 years	2 years	2 years