



	SWITCH POE IP-9-11-L2 8-PORT ATTE	AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE16D8T-IT3F(2.8MM) - 1080p Hikvision
		
	181.01 EUR 181.01 EUR	93.02 EUR 93.02 EUR
Standard	...	AHD / HD-CVI / HD-TVI / PAL
Sensor	...	Progressive Scan CMOS
Matrix size	...	2.1 Mpx
LAN ports	<ul style="list-style-type: none"> • 1 x RJ45 10/100 Base-T - Uplink • 9 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE 	...
Management	—	...
LED diodes	Power, LAN	...
Resolution	...	1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI 960 x 576 - 960H @ PAL
Transmission speed	10 / 100 Mbps : 1 Port LAN + 9 LAN & PoE ports	...
Lens	...	2.8 mm
View angle	...	<ul style="list-style-type: none"> • 104 ° (manufacturer data) • 100 ° (our tests result)
Range of IR illumination	...	60 m
IR illuminator power adjustment	...	Automatic
Maximal output power	<ul style="list-style-type: none"> • 40 W @ Passive PoE - 1 ... 4 ports, • 70 W @ Passive PoE - Port 5, • 30 W @ PoE (802.3af/at) - 1 ... 5 ports 	...
Maximal total power	96 W	...
Video output	...	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI / PAL, BNC socket
OSD menu	...	OSD menu available via recorder
Operation modes	<ul style="list-style-type: none"> • Normal : 100 m @ 10/100 Mb/s - 1 ... 5 ports • Long Range : 280 m @ 10 Mb/s - 1 ... 4 ports ; 100 m @ 10/100 Mb/s - Port 5 	...

Main features	...	<ul style="list-style-type: none"> • WDR \geq 130 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • ICR - Movable InfraRed filter • BLC - Back Light Compensation • AGC - Automatic Gain Control • Auto White Balance • Motion Detection - max. 4 zones • Privacy zones - max. 4 • Mirror - Mirror image • Sharpness - sharper image outlines
Power consumption	...	\leq 3.4 W
Housing	...	Compact, Metal
Main features	<ul style="list-style-type: none"> • Possible cascading device connection (power transmission between devices using Passive PoE via LAN 5 port) • The LAN 5 (PoE IN/OUT) port can be used to power PoE devices as well as to draw power from other devices • The output PoE voltage is equal to the input voltage • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 5 ports • The modular design streamlines service tasks and enables quick and easy system expansion • The raster system of module assembly facilitates the expansion of the device by further modules • The ABOX-L2 mounting enclosure is equipped with 11 cable entries with glands in the 10 x M16 + 1 x M20 arrangement 	...

Color	...	White + Black
Power supply	230 V AC - cable terminals	12 V DC / 280 mA
"Index of Protection"	...	IP67
Operation temp	...	-40 °C ... 60 °C
Weight	1.05 kg	0.56 kg
Dimensions	248 x 222 x 96 mm	226 x 87 x 82 mm
Supported languages	...	English
Manufacturer / Brand	ATTE	Hikvision
SAP Code	...	300511195
Guarantee	3 years	3 years