

| | ROUTER RUT140 Wi-Fi 2.4 GHz 300 Mbps Teltonika | TURNBUCKLE VANT-5/PL | CRIMP SOCKET SMA- G/ZAC.H-155 | SIDE MAGNETIC CONTACT B-3 SATEL |
|----------------------------------|---|---|--|---|
| |  |  |  |  |
| | 85.64 AUD 85.64 AUD | 2.28 AUD 2.28 AUD | 2.53 AUD 2.53 AUD | 12.50 AUD 12.50 AUD |
| Frequency range | 2.4 GHz | ... | ... | ... |
| Application | ... | Steel lines | ... | ... |
| Detection | ... | ... | ... | Opening the door or window |
| Connector type | ... | ... | SMA Socket | ... |
| Maximum reed switched voltage | ... | ... | ... | 100 V |
| Antenna type | SMA-RP socket - without antenna | ... | ... | ... |
| Attachment of connector elements | ... | ... | Crimping | ... |
| Maximal switched current | ... | ... | ... | 400 mA |
| Make distance | ... | ... | ... | 38 mm |
| Standards | IEEE 802.11 b/g/n | ... | ... | ... |
| Shield fastening | ... | ... | Crimping | ... |
| Break distance | ... | ... | ... | 42 mm |
| Wire mounting | ... | ... | Soldering | ... |
| Application | ... | ... | Coaxial cable | ... |
| Color | ... | ... | ... | Silver |
| Cable diameter | ... | ... | max. 6.1 mm | ... |
| Impedance | ... | ... | 50 Ω | ... |
| Material | ... | Metal | Metal | ... |
| Baud rates | 11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps | ... | ... | ... |
| Example of application | ... | ... | • TRI-LAN/100 • H-155 | ... |
| LAN ports | 1 x 10 / 100 Mbps | ... | ... | ... |
| WAN interface | 1 x 10 / 100 Mbps | ... | ... | ... |
| LED indicators | Power, WAN, LAN | ... | ... | ... |
| LTE | — | ... | ... | ... |
| QSS | — | ... | ... | ... |
| WDS | — | ... | ... | ... |
| DHCP server | ✓ | ... | ... | ... |
| DDNS | Support > 25 | ... | ... | ... |
| Operation modes | Access Point, Station | ... | ... | ... |

| | | | | |
|----------------------|---|-----|-----|-----|
| Protections | <ul style="list-style-type: none"> • WPA2-Enterprise - PEAP • WPA-PSK/WPA2-PSK • WPA-EAP • WPA3-SAE • WPA3-EAP • OWE • AES-CCMP • TKIP • WEP • EAP-TLS • Auto Cipher modes • Client separation • SSID hiding • MAC addresses filtering • Firewall • Support DDOS, SYN, SSH, HTTP/HTTPS defence • White list / Black list | ... | ... | ... |
| Management interface | Web browser, Teltonika RMS application | ... | ... | ... |
| Default IP address | 192.168.1.1 | ... | ... | ... |
| Operating system | RutOS (Linux OS based) | ... | ... | ... |
| Firmware update | ✓ | ... | ... | ... |



| | | | | |
|-------------------------------|--|--|--|---------------------------|
| Main features | <ul style="list-style-type: none"> • Support for Mesh technology, • Compliance with the Modbus, DLMS, DNP3, OPC UA protocol • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Static / dynamic routing • Support for VoIP technology, • View topology and network status • WMM support (QoS mechanism of the 802.11e standard) • DHCP Relay support • Load balance • Ability to work as a Hotspot, • VLAN support • VPN networks: IPsec VPN, L2TP VPN, PPTP VPN, Open VPN • Compliance with the MQTT protocol • SNMP v1/v2/v3/Trap • Support for IoT (Internet of Things) systems, • Configuration using the Teltonika RMS application • RESET button • Durable aluminum housing • Shock-proof • Industrial wide temperature design. • Mounting on DIN rail, • 3-pin industrial power socket, • Wide range of supported supply voltages • Grounding • "Index of Protection" : IP30 | <ul style="list-style-type: none"> • Screw diameter 5 mm • Work load 50 kg • Corrosion resistance | <ul style="list-style-type: none"> • Wide frequency range • Corrosion resistance • To crimp use the crimping tool HT-301C | Rugged, metal sealed body |
| Certificates | CE, UKCA, FCC, WEEE | ... | ... | ... |
| Power supply | <ul style="list-style-type: none"> • 9 ... 30 V DC • 9 ... 30 V DC - Passive PoE, Powering from LAN1 | ... | ... | ... |
| Power consumption | ≤ 2 W | ... | ... | ... |
| Operation temp | -40 °C ... 75 °C | ... | ... | ... |
| Permissible relative humidity | 10 % ... 90 % (non-condensing) | ... | ... | ... |
| Weight | 0.15 kg | 0.05 kg | 0.010 kg | 0.05 kg |
| Dimensions | 123 x 69 x 25 mm | 140 x 20 x 7 mm | ... | 50 x 17 x 9.8 mm |
| Manufacturer / Brand | Teltonika | ... | ... | SATEL |
| Guarantee | 2 years | 2 years | 2 years | 2 years |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00