



	<a href="#">IP SPEED DOME CAMERA OUTDOOR DS-2DE5230W-AE - 1080p 4.3 ... 129 mm Hikvision</a>	<a href="#">PROXIMITY READER WITH KEYPAD + RFID DHI-ASI1201A-D DAHUA</a>
		
	1028.77 EUR 1028.77 EUR	137.73 EUR 137.73 EUR
Cards support	...	Unique EM 125kHz
Standard	TCP/IP	...
Reading distance of prox-keys	...	max. 8 cm
Sensor	1/2.8 " Progressive Scan CMOS	...
Autonomous operation	...	✓
Keyboard built-in	...	✓
Matrix size	2.1 Mpx	...
Communication	...	<ul style="list-style-type: none"> <li>• Ethernet</li> <li>• RS-485</li> <li>• Wiegand</li> </ul>
Tamper output	...	✓
Resolution	1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p	...
Maximal current consumption	...	200 mA
Main features	...	<ul style="list-style-type: none"> <li>• 30000 indexed users,</li> <li>• Events memory : 150 000,</li> <li>• Touch control keys,</li> <li>• Blue backlight of the keys</li> </ul>
Operation temp	...	-5 °C ... 55 °C
Permissible relative humidity	...	≤ 95 % (non-condensing)
Scanning system	Progressive	...
Lens	4.3 ... 129 mm	...
View angle	<ul style="list-style-type: none"> <li>• 66 ° ... 2.1 ° (manufacturer data)</li> <li>• 59 ° ... 3.3 ° (our tests result)</li> </ul>	...
Optical zoom	x 30	...
Digital zoom	x 16	...
Min. illumination	<ul style="list-style-type: none"> <li>• 0.05 Lux @ F1.6 (color),</li> <li>• 0.01 Lux @ F1.6 (B/W)</li> </ul>	...
Video output	—	...
Preset rotation speed	300 °/s (horizontal) 200 °/s (vertical)	...
Rotation speed (manual control)	0.1 °/s ... 250 °/s (horizontal) 0.1 °/s ... 150 °/s (vertical)	...
Horizontal rotation range	360 ° continuous	...

Vertical rotation range	-5 ° ... 90 °	...
RS-485 interface	—	...
Number of presets	300	...
Horizontal scan	✓	...
Route settings	8	...
Image compression method	H.265 / H.265+ / H.264 / H.264+ / MJPEG	...
Bitrate	32 ... 16384 kbps	...
Alarm inputs / outputs	2 / 1	...
Audio	<ul style="list-style-type: none"> <li>• External microphone input,</li> <li>• Audio output,</li> <li>• Audio detection</li> </ul>	...
Main stream frame rate	25 fps @ 1080p	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	IPv4/IPv6, HTTP, HTTPS, IEEE 802.1x, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE	...
WEB Server	Built-in, NVR compliance	...
Max. number of on-line users	20	...
ONVIF	16.12	...
Memory card slot	Micro SD memory cards up to 128GB support (possible local recording)	...
Main features	<ul style="list-style-type: none"> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• D-WDR - Wide Dynamic Range</li> <li>• Parking action - this function enables to locate the camera to specific position automatically if operator doesn't operate the controller for some time</li> <li>• Configurable Privacy Zones - 8</li> <li>• ICR - Movable InfraRed filter</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• Sharpness - sharper image outlines</li> <li>• Mirror - Mirror image</li> <li>• Day/Night mode (color/b&amp;w/auto)</li> <li>• Audio detection</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion</li> </ul>	...
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">iVMS-4500</a> or <a href="#">Hik-Connect</a></li> <li>• iOS (iPhone): Free application <a href="#">iVMS-4500</a> or <a href="#">Hik-Connect</a></li> </ul>	...
Default IP address	192.168.1.64	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80	...

PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Mobile client access ports	8000	...
Port ONVIF	80	...
RTSP URL	<ul style="list-style-type: none"> <li>• Main stream rtsp://192.168.1.64:554/Streaming/Channels/101/ - RTSP - without authorization</li> <li>rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization</li> <li>• Sub stream rtsp://192.168.1.64:554/Streaming/Channels/102/ - RTSP - without authorization</li> <li>rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization</li> </ul>	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3at),</li> <li>• 24 V AC / 2.2 A (power adapter included)</li> </ul>	9 ... 15 V DC
Power consumption	≤ 22 W	...
Housing	Speed Dome Metal	Plastic
Color	White	Silver / Black
"Index of Protection"	IP66	IP55
Vandal-proof	—	...
Operation temp	-30 °C ... 65 °C	...
Weight	2.9 kg	0.23 kg
Dimensions	Ø 220 x 305 mm	97 x 151 x 17 mm
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian	...
Manufacturer / Brand	Hikvision	DAHUA
SAP Code	301309545	...
Guarantee	3 years	3 years