




	MULTI-SOCKET PLUG LE-50637 3680 W LEGRAND	PLUG-IN MODULE FOR OVERVOLTAGE LIMITER LE-412297 2 TYPE 20 kA LEGRAND	ACCESS CONTROLLER ASC2202B-S DAHUA
			
	26.39 AUD 26.39 AUD	37.65 AUD 37.65 AUD	346.32 AUD 346.32 AUD
Number of served transitions	2 (one-way)
Support	DAHUA
Rated voltage	230 V / 50 Hz	230 / 400 V AC, 50 / 60 Hz	...
Number of supported readers	4 pcs
Maximal total load	3680 W
Battery backup support	—
Total maximal current	16 A
Maximal voltage	...	320 V AC, 50 / 60 Hz	...
Number of outlets	2 pcs 2P+Z
Output lines	2 pcs - Relay
Grounding	✓
Class	...	2 type (Class C)	...
Color	White / Gray
Protection level Up	...	1.2 kV @ 8/20 µs (T2)	...
Communication	<ul style="list-style-type: none"> • RS-485, • Ethernet, • Wiegand
Nominal discharge current	...	5 kA @ 8/20 µs (T2)	...
Maximum stroke current	...	20 kA @ 8/20 µs (T2)	...
Operation state indication	...	✓	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3at), • 12 V DC / 4 A
Housing	Plastic	Plastic	...

Main features	...	Varistor	<ul style="list-style-type: none"> • 100000 indexed users • History of 500000 events • Remote programming from PC • Function of protection against multiple use of the same card for access (anti-passback) • Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value • Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress • Possibility to mount on a wall, or on the DIN TS-35 rail
Default IP address	192.168.0.2
Default admin user / password	admin / - The administrator password should be set at the first start
Operation temp	-30 °C ... 60 °C
Permissible relative humidity	5 % ... 90 % (non-condensing)
Weight	0.15 kg	0.042 kg	0.27 kg
Dimensions	110 x 61 x 101 mm	62 x 54 x 17 mm	155 x 116 x 50 mm
Manufacturer / Brand	LEGRAND	LEGRAND	DAHUA
Guarantee	2 years	2 years	3 years