






| | EXPANSION PLUG KW-10/SX60 KLIMAS | EXPANSION PLUG KW-8/SX50 KLIMAS | EXPANSION PLUG JPK-12X220/M5 EBOLT | STYROFOAM PLUG SM-50/EPN*P4 Elektro-Plast | WORK GLOVES WC-422/M Bee-Smart WONDER GRIP | CABLE PAIR DETECTOR WITH RJ-45 CABLE TESTER UT-682 UNI-T | RJ45 CONNECTOR TOOL KIT NS-468/KIT | USB SOCKET TESTER UT-658 UNI-T |
|-------------------------------|---|---|--|---|--|---|---|---|
| |  |  |  |  |  |  |  |  |
| | 46.15 HUF 46.15 HUF | 47.12 HUF 47.12 HUF | 788.46 HUF 788.46 HUF | 374.04 HUF 374.04 HUF | 2255.77 HUF 2255.77 HUF | 11832.69 HUF 11832.69 HUF | 3700.00 HUF 3700.00 HUF | 4060.58 HUF 4060.58 HUF |
| Device type | ... | ... | ... | ... | ... | ... | ... | Power meter via USB port |
| Input socket type | ... | ... | ... | ... | ... | ... | ... | 1 x USB-A plug |
| Output socket type | ... | ... | ... | ... | ... | ... | ... | 1 x USB-A socket |
| LCD display | ... | ... | ... | ... | ... | ... | ... | 1.22 " |
| In package | ... | ... | ... | 4 pcs The price for package | ... | ... | ... | ... |
| Length | ... | ... | ... | 49 mm | ... | ... | ... | ... |
| Drilling diameter | 10 mm | 8 mm | 12 mm | ... | ... | ... | ... | ... |
| Tested cables | ... | ... | ... | ... | ... | UTP, FTP, YTKSY - RJ45 (8P8C), RJ11 (6P4C) | UTP, FTP, YTKSY - RJ45 (8P8C), RJ11 (6P4C), RJ12 (6P6C) | ... |
| DC voltage measurement | ... | ... | ... | ... | ... | ... | ... | 3 ... 9 V ± 1 % |
| Expansion plug length | 50 mm | 50 mm | 215 mm | ... | ... | ... | ... | ... |
| Diameter | ... | ... | ... | Ø 20 mm / Ø 24 mm | ... | ... | ... | ... |
| Thickness of the Styrofoam | ... | ... | ... | ≥ 50 mm | ... | ... | ... | ... |
| Color | ... | ... | ... | ... | Black + Blue | ... | ... | ... |
| DC current measurement | ... | ... | ... | ... | ... | ... | ... | 0 ... 3 A ± 1 % |
| Screw dimensions | Ø 5 x 60 mm, PZ-2 | Ø 5 x 50 mm, PZ-2 | Ø 8 x 220 mm, Internal thread M5 | ... | ... | ... | ... | ... |
| Diameter of the screw | ... | ... | ... | Ø 4 mm ... Ø 5 mm | ... | ... | ... | ... |
| Material | • Expansion plug, Polypropylene • Screw, Steel galvanized | • Expansion plug, Polypropylene • Screw, Steel galvanized | • Expansion plug, Polypropylene • Screw, Steel galvanized • mounting screw, Steel galvanized | ... | Polyester + latex coating (palm coated) | ... | ... | ... |
| Battery capacity measurement | ... | ... | ... | ... | ... | ... | ... | 0 ... 9999 mAh |
| Screw | ... | ... | Ø 5 x 16 mm | ... | ... | ... | ... | ... |
| Housing | ... | ... | ... | ... | ... | ... | ... | Plastic |
| Power supply | ... | ... | ... | ... | ... | 2 x 9V, type 6F22 battery (included) | Battery 9 V 6LR61 (not included) | 5 V DC - Port USB |
| Operation temp | ... | ... | ... | ... | ... | 0 °C ... 40 °C | ... | ... |
| Permissible relative humidity | ... | ... | ... | ... | ... | 20 % ... 75 % | ... | ... |
| Main features | ... | ... | ... | ... | • Thermal protection : 100 °C (X1XXXX), • Ergonomics and comfort • High grip • Soft coating | • Test for the presence of a short circuit, open circuit • Polarity indicator for telephone wire pairs : ± (5V ... 52V) • The maximum length of the telephone line : 3000 m • Optical - sound signaling • Low battery indicator | ... | ... |
| Application | • Concrete • Solid clay brick • Solid sand-lime brick | • Concrete • Solid clay brick • Solid sand-lime brick | for Styrofoam 150 mm | ... | • Construction and public works, • Warehousing - packing and logistics, • DIY, • Assembly | ... | Plug RJ45 (8P8C) , Plug RJ12 (6P6C) , Plug RJ11 (6P4C) / DEC | ... |
| Supported norms | ... | ... | ... | ... | • EN 388:2016 - Mechanical protection 3131X • EN 407:2004 - Thermal protection X1XXXX | ... | ... | ... |
| Size | ... | ... | ... | ... | 8 / M | ... | ... | ... |
| Weight | ... | ... | ... | 0.004 kg / 1 pcs | ... | • 0.11 kg - Transmitter • 0.14 kg - Receiver | 0.12 kg 0.77 kg (total) | 0.02 kg |
| Dimensions | ... | ... | ... | ... | ... | • 125 x 48 x 29 mm - Transmitter • 194 x 50 x 30 - Receiver | 101 x 107 x 28 mm 260 x 170 55 mm (case) | 84 x 29 x 12 mm |
| Manufacturer / Brand | KLIMAS | KLIMAS | EBOLT | Elektro-Plast Nasielsk | WONDER GRIP | UNI-T | ... | UNI-T |
| Guarantee | 2 years | 2 years | 2 years | 2 years | ... | 2 years | 2 years | 2 years |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00