




	TV OR MONITOR MOUNT BRATECK-LCD-142A	AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE16D8T- IT3F(2.8MM) - 1080p Hikvision	TOGGLE PLUG DUOTEC-10/SPH Fischer
			
	15.78 EUR 15.78 EUR	92.55 EUR 92.55 EUR	1.11 EUR 1.11 EUR
Material	<ul style="list-style-type: none"> • Toggle Plug, Nylon • Screw, Steel galvanized
Standard	...	AHD / HD-CVI / HD-TVI / PAL	...
Drilling diameter	10 mm
Sensor	...	Progressive Scan CMOS	...
Mounting standard	VESA 75, 100, 150, 200, 200x100
Expansion plug length	40 mm
Matrix size	...	2.1 Mpx	...
Screen size range	17 " ... 37 "
Screw dimensions	Ø 5 x 60 mm
Bearing capacity	20 kg
Mounting panel thickness	9.5 ... 55 mm
Distance from mounting surface	70 ... 250 mm from wall
Cavity depth	min. 40 mm
Tilt adjustment	-15 ° ... 15 °
Resolution	...	1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI 960 x 576 - 960H @ PAL	...
Lens	...	2.8 mm	...
Horizontal rotation	Articulated arm with two swivels in range -90 ° ... 90 ° each
Application	<ul style="list-style-type: none"> • plasterboard • Gypsum fibreboard • OSB board • MDF board • Concrete • Solid clay brick • Solid sand-lime brick
Rotation in the plane of the screen	360 °
View angle	...	<ul style="list-style-type: none"> • 104 ° (manufacturer data) • 100 ° (our tests result) 	...
Range of IR illumination	...	60 m	...

IR illuminator power adjustment	...	Automatic	...
Video output	...	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI / PAL, BNC socket	...
OSD menu	...	OSD menu available via recorder	...
Main features	...	<ul style="list-style-type: none"> • WDR ≥ 130 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • ICR - Movable InfraRed filter • BLC - Back Light Compensation • AGC - Automatic Gain Control • Auto White Balance • Motion Detection - max. 4 zones • Privacy zones - max. 4 • Mirror - Mirror image • Sharpness - sharper image outlines 	...
Power supply	...	12 V DC / 280 mA	...
Power consumption	...	≤ 3.4 W	...
Housing	...	Compact, Metal	...
Color	Black	White + Black	...
"Index of Protection"	...	IP67	...
Operation temp	...	-40 °C ... 60 °C	...
Weight	1.1 kg	0.56 kg	...
Dimensions	195 x 119 x (70 ... 250) mm	226 x 87 x 82 mm	...
Supported languages	...	English	...
Manufacturer / Brand	...	Hikvision	Fischer
SAP Code	...	300511195	...
Guarantee	2 years	3 years	2 years