



	ACCESS CONTROLLER MODULE MC16-PAC-EX-3 ROGER	POWER DISTRIBUTION UNIT ACAR-F5/FA/RACK
		
	584.52 GBP 584.52 GBP	23.04 GBP 23.04 GBP
Number of served transitions	3	...
Inputs	18	...
Rated voltage	...	230 V AC / 50 Hz
Outputs	12	...
Nominal load current	...	max. 10 A (total)
Maximal total load	...	2300 W
Number of users	max. 12000 - Number of identifiers	...
Nominal voltage of surge suppressor	...	250 V / 50 Hz
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.	...
Protection level of surge suppressor	...	≤ 1.3 kV (L/N)
Number of permissions per ID	100	...
Number of outlets	...	5 grounded outlets 10A/250V
Buffer memory	8 000 000 events buffer	...
MCT readers support	16 pcs	...
Automatic delayed fuse	...	10 A / 250 V
Nominal stroke current	...	2 kA (L/N) - 8/20 μs
Readers connections	4 pcs - Wiegand / PRT	...
Number of login points	6	...
Maximum stroke current	...	10 kA (L/N) - 8/20 μs 2 type
Number of access terminals	12	...
Response time	...	< 25 ns
Number of access zones	6	...
Number of alarm zones	6	...
Switch	...	two-way, with light indication
Number of automation nodes	6	...
Battery backup support	12 V / 7 Ah	...
Housing	...	RACK 19", 1U, Plastic - non-flammable

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Communication	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RS-485 interface • RACS 5 v2 (Roger) 	...
Length of the cable	...	2.9 m
Main features	<ul style="list-style-type: none"> • Integrated support in VISO EX software • Functions in the VISO EX system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system - unlimited - division of the system into partitions operated by independent operators - tool for integration with RACS5 (API) systems - integration with many systems (elevator systems, building applications, SMS, BMS, PSIM, VMS, Active Directory systems) 	<ul style="list-style-type: none"> • Current paths shutters • DC filter to eliminate interferences : ≤ 35 dB
Power supply	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC 	...
Operation temp	5 °C ... 40 °C	...
Permissible relative humidity	10 % ... 95 % (non-condensing)	...
Weight	0.14 kg	0.93 kg
Dimensions	175 x 72 x 30 mm	484 x 54 x 55 mm
Manufacturer / Brand	ROGER	...
Guarantee	3 years	2 years