

	<a href="#">POWER DISTRIBUTION UNIT AK-SP-05U (5 OUTLETS + 2 USB) AKYGA</a>	<a href="#">IP VANDALPROOF CAMERA IPC-HFW5831E-ZE-2712 - 8.3 Mpx, 4K UHD 2.7 ... 12 mm - MOTOZOOM DAHUA</a>
		
	14.19 EUR 14.19 EUR	533.53 EUR 533.53 EUR
Standard	...	TCP/IP
Sensor	...	1/2.5 " STARVIS™ CMOS
Rated voltage	230 V AC / 50 Hz	...
Total maximal current	10 A	...
Matrix size	...	8.3 Mpx
Maximal total load	2500 W	...
Response time	< 25 ns	...
Number of outlets	<ul style="list-style-type: none"> <li>• 5 grounded outlets 10A/250V,</li> <li>• 2 USB ports 2A/5V</li> </ul>	...
Automatic delayed fuse	10 A / 250 V	...
Nominal voltage of surge suppressor	250 V / 50 Hz	...
DC filter to eliminate interferences	RFI ≤ 10 dB	...
Maximum stroke current	4.5 kA	...
Maximum energy absorption	150 J	...
Switch	with light indication	...
Length of the cable	1.5 m	...
Operation temp	5 °C ... 50 °C	...
Resolution	...	3840 x 2160 - 8.3 Mpx, 4K UHD 3072 x 2048 - 6.3 Mpx , 3072 x 1728 - 5.3 Mpx , 2592 x 1944 - 5.0 Mpx , 2688 x 1520 - 4.0 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3.0 Mpx , 1920 x 1080 - 1080p 1280 x 1024 - 1.4 Mpx 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Lens	...	2.7 ... 12 mm - Motozoom
View angle	...	<ul style="list-style-type: none"> <li>• 110 ° ... 40 ° (manufacturer data)</li> <li>• 102 ° ... 38 ° (our tests result)</li> </ul>
Range of IR illumination	...	50 m
S/N ratio	...	> 50 dB
RS-485 interface	...	—
Memory card slot	...	Micro SD memory cards up to 128GB support (possible local recording)
Image compression method	...	H.265 / H.264H / MJPEG
Alarm inputs / outputs	...	2 / 1

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Audio	...	<ul style="list-style-type: none"> <li>• External microphone input</li> <li>• Audio output</li> <li>• Bi-directional audio streaming support</li> <li>• Audio detection</li> </ul>
Bitrate	...	24 kb/s ... 10240 kb/s - H.264 14 kb/s ... 9984 kb/s - H.265
Network interface	...	10/100 Base-T (RJ-45)
Network protocols	...	HTTP, HTTPS, ARP, IPv4/IPv6, TCP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, UPnP, NTP, QoS, Bonjour, IEEE 802.1x, Multicast, ICMP, IGMP, SNMP
WEB Server	...	Built-in, Web Viewer
Max. number of on-line users	...	20
ONVIF	...	16.12
Main stream frame rate	...	15 fps @ 8.3 Mpx 25 fps @ 5.3 Mpx
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">DMSS</a></li> <li>• iOS (iPhone): Free application <a href="#">DMSS</a></li> </ul>
Default admin user / password	...	admin / admin
Default IP address	...	192.168.1.108
Web browser access ports	...	80, 37777
PC client access ports	...	37777
Mobile client access ports	...	37777
Port ONVIF	...	80
RTSP URL	...	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Main features	...	<ul style="list-style-type: none"> <li>• Motozoom lens</li> <li>• WDR - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• ICR - Movable InfraRed filter</li> <li>• Motion Detection</li> <li>• IVS analysis : crossing the line (tripwire), intrusion, abandoned/missing object, face detection</li> <li>• WB - White Balance (ATW/AWB/manual/indoor/outdoor)</li> <li>• BLC - configurable Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• Configurable Privacy Zones</li> <li>• D-ZOOM - Digital Zoom</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> <li>• Adaptive adjusting of the IR illuminator power to the lens zoom and outdoor light conditions</li> </ul>
Power supply	...	<ul style="list-style-type: none"> <li>• PoE (802.3at),</li> <li>• ePoE,</li> <li>• 12 V DC / 1080 mA</li> </ul>
Power consumption	...	≤ 12.95 W
Housing	Plastic (ABS)	Compact - Metal



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Color	Black	White
Vandal-proof	...	IK10
"Index of Protection"	...	IP67
Operation temp	...	-30 °C ... 60 °C
Weight	0.318 kg	1.07 kg
Dimensions	305 x 50 x 40 mm	274 x 95 x 95 mm
Supported languages	...	English, Polish
Manufacturer / Brand	AKYGA	DAHUA
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00