

| | | |
|--------------------------|---|---|
| | IP CAMERA DS-2CD2046G2-I(2.8mm) ACUSENSE - 5 Mpx Hikvision | SWITCH POE IPB-5-10A-S4 5-PORT ATTE |
| |  |  |
| | 922.00 PLN 922.00 PLN | 324.19 PLN 324.19 PLN |
| Standard | TCP/IP | ... |
| Sensor | 1/3 " Progressive Scan CMOS | ... |
| Scanning system | Progressive | ... |
| Matrix size | 5 Mpx | ... |
| LAN ports | ... | <ul style="list-style-type: none"> • 1 x RJ45 10/100 Base-T - Uplink • 5 x RJ45 10/100 Base-T - PoE (802.3af/at) / Passive PoE |
| Management | ... | — |
| LED diodes | ... | Power, LAN |
| Transmission speed | ... | 10 / 100 Mbps : 1 Port LAN + 5 LAN & PoE ports |
| Resolution | 2592 x 1944 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p | ... |
| Lens | 2.8 mm | ... |
| View angle | <ul style="list-style-type: none"> • 103 ° (manufacturer data) • 94 ° (our tests result) | ... |
| Maximal output power | ... | <ul style="list-style-type: none"> • 40 W @ Passive PoE - 1 ... 5 ports, • 30 W @ PoE (802.3at) - 1 ... 5 ports • 15.4 W @ PoE (802.3af) - 1 ... 5 ports |
| Maximal total power | ... | 90 W |
| Compression | H.265+ / H.265 / H.264+ / H.264 / MJPEG | ... |
| Range of IR illumination | 40 m | ... |
| Alarm inputs / outputs | — | ... |
| Audio | — | ... |
| Memory card slot | Micro SD memory cards up to 256GB support (possible local recording) | ... |
| Main stream frame rate | 20 fps @ 5 Mpx 25 fps @ 4 Mpx | ... |
| Network interface | 10/100 Base-T (RJ-45) | ... |

| | | |
|-------------------------------|--|--|
| Main features | ... | <ul style="list-style-type: none"> • Supported PoE devices: 802.3af/at, Passive PoE • Possibility to connecting in cascade • Efficiency : 93 % @ 90 W • 5 polymer fuses - PoE • Possibility to power other devices powered from 55 V (screw connection) • PSU thermal protection • Short-circuit protection • Overload protection • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 4 ports • Switch has built-in a 55 V DC power supply adapter with power of 90 W • "Index of Protection" : IP55 |
| Network protocols | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, IEEE 802.1x, QoS, IPv4, IPv6, UDP, Bonjour, SSL, TLS, PPPoE, SNMP, ARP | ... |
| WEB Server | Built-in | ... |
| Max. number of on-line users | 6 | ... |
| ONVIF | 18.12 | ... |
| Mobile phones support | Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application iVMS-4500 or Hik-Connect • iOS (iPhone): Free application iVMS-4500 or Hik-Connect | ... |
| Default IP address | 192.168.1.64 | ... |
| Default admin user / password | admin / - The administrator password should be set at the first start | ... |
| Web browser access ports | 80 | ... |
| PC client access ports | Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application | ... |
| Mobile client access ports | 8000 | ... |
| Port ONVIF | 80 | ... |
| RTSP URL | <ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ <ul style="list-style-type: none"> • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ | ... |
| RS-485 interface | — | ... |

| | | |
|-----------------------|---|--|
| Main features | <ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • Day/night mode • ICR - Movable InfraRed filter • WB - White Balance • AGC - Automatic Gain Control • Possibility to change the resolution, quality and bit rate • Sharpness - sharper image outlines • Configurable Privacy Zones • Motion Detection • Mirror - Mirror image • Filtering of false alarms based on the recognition of persons and vehicles • Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, scene changing, face detection, advanced face capture features | ... |
| Power supply | <ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 500 mA | 180 ... 240 V AC - Built-in switching power supply |
| Power consumption | <ul style="list-style-type: none"> • ≤ 7 W @ PoE (802.3af) • ≤ 6 W @ 12 V DC | ... |
| Housing | Compact, Metal | ... |
| Color | White | ... |
| "Index of Protection" | IP67 | ... |
| Operation temp | -30 °C ... 60 °C | ... |
| Supported languages | Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Vietnamese, Italian | ... |
| Weight | 0.48 kg | 0.43 kg |
| Dimensions | Ø 70 x 162 mm | 158 x 118 x 77 mm |
| Manufacturer / Brand | Hikvision | ATTE |
| SAP Code | 311312251 | ... |
| Guarantee | 3 years | 3 years |