



	<a href="#">COAXIAL CABLE TRISET-PLUS/500 Dca LSZH A+</a>	<a href="#">SINGLE-MODE PATCHCORD PC-2LC/2SC-2 2 m</a>
		
	2.38 PLN 2.38 PLN	14.72 PLN 14.72 PLN
Connector type	...	LC/UPC <-> SC/UPC
Fiber optic type	...	9 / 125 μm
In section	<b>500 m . Price for 1m when buying a whole roll</b>	...
Max. connector insertion loss	...	0.19 dB
Coaxial cable	TRISSET	...
Inner conductor	Ø 1.13 mm Cu Wire	...
Dielectric	Ø 4.8 mm (physical foam)	...
Length	...	2 m
Shield	<ul style="list-style-type: none"> <li>• Foil : Al/PET/SY - Internal</li> <li>• Foil : Al/PET - External</li> </ul>	...
Braid	81 % Al wire	...
Outer coating	Ø 6.85 mm PVC LSZH	...
Coating color	White	...
Minimal bend radius	70 mm	...
Impedance	75 Ω	...
Capacity	52 pF/m	...
Resistance of the inner conductor for DC current	16.85 Ω/km	...
Dielectric resistance	2500 MΩ/km	...
Screening efficiency	<ul style="list-style-type: none"> <li>&gt; 95 dB @30 ... 1000 MHz</li> <li>&gt; 85 dB @1 ... 2 GHz</li> <li>&gt; 75 dB @2 ... 3 GHz</li> </ul>	...
Shortening wave coefficient	84 %	...
Weight	41.4 kg/km	...
Main features	<ul style="list-style-type: none"> <li>• low attenuation</li> <li>• perfect matched</li> <li>• high screening efficiency</li> <li>• LSZH (Low Smoke Zero Halogen) coating - means small amount of toxic gases emitted during combustion</li> </ul>	<ul style="list-style-type: none"> <li>• Made according to the requirements: G.652 D</li> <li>• LSZH (Low Smoke Zero Halogen) coating - means small amount of toxic gases emitted during combustion</li> <li>• Cable diameter : 1.9 mm</li> </ul>
Guarantee	2 years	2 years