




	THERMOSTAT FOR FAN COOLERS KTS-011	TV OR MONITOR MOUNT AX-FLEXI-25	WEATHER STATION UT-A13T UNI-T	CABLES TESTER HDMI UT-681-HDMI UNI-T
				
	48.41 DKK 48.41 DKK	29.83 DKK 29.83 DKK	102.50 DKK 102.50 DKK	167.13 DKK 167.13 DKK
Sensor type	Bimetallic
Tested cables	HDMI, mini HDMI
Measurement	Temperature / relative humidity	...
Maximal power voltage	250 V AC
Maximal current consumption	10 A
Mounting standard	...	VESA 75, 100
Measurement range	-10 °C ... 50 °C ± 1 °C	...
Temperature set range	0 °C ... 60 °C
Screen size range	...	10 " ... 25 "
Bearing capacity	...	15 kg
Distance from mounting surface	...	59 mm
Hysteresis	7 °C ± 4 °C
Measurement of humidity	20 % ... 95 % ± 5 %	...
Tilt adjustment	...	0 ° ... 15 °
"Index of Protection"	IP20
Horizontal rotation	...	-45 ° ... 45 °
Mounting	DIN rail 35 mm
Rotation in the plane of the screen	...	—
Main features	<ul style="list-style-type: none"> • LCD display • Digital sensor • Alarm function • Calendar function • Selectable measurement unit: °C / °F • Wall mounting • Integrated stand 	<ul style="list-style-type: none"> • Test for the presence of a short circuit, open circuit • Single / full scan mode • Automatic shutdown after 10 minutes of inactivity • Low battery level alarm
Power supply	1 x battery LR3 (AAA) (included)	9V, type 6F22 battery (included)
Color	...	Black	White	...
Operation temp	-20 °C ... 80 °C	...	-10 °C ... 50 °C	...
Permissible relative humidity	max. 90 % (non-condensing)	...
Weight	0.042 kg	0.31 kg	0.106 kg	0.132 kg
Dimensions	60 x 43 x 33 mm	130 x 120 x 59 mm	Ø 130 x 78 mm x 22 mm	103 x 96 x 29 mm
Manufacturer / Brand	UNI-T	UNI-T
Guarantee	2 years	2 years	2 years	2 years