



	COUPLER WW-5.5	POWER DISTRIBUTION UNIT ACAR-ECO-PLUS (6 OUTLETS)
		
	0.48 EUR 0.48 EUR	58.77 EUR 58.77 EUR
Maximal load power	...	2300 W
Nominal voltage	...	230 V AC / 50 Hz
Fuse	...	10 A / 250 V
Switch	...	two-way
Leak current	...	< 0.5 mA
Connector type	Coupler Plug 2.1 : 5.5 mm / Plug 2.1 : 5.5 mm	...
Response time	...	< 25 ns
Material	Metal / PET	...
Nominal voltage of surge suppressor	...	250 V
Protection level	...	1.3 kV (L/N)
Main features	<ul style="list-style-type: none"> • Very easy and quick assembly • Corrosion resistance 	...
Nominal stroke current	...	2 kA (L/N) - (8/20µs)
Maximum stroke current	...	6.5 kA (L/N) - (8/20µs)
Electric shock protection system	...	Ground connectors (pins) connected with ground wire of AC mains
Housing	...	Plastic - non-flammable
Number of output outlets	...	<ul style="list-style-type: none"> • 1 MASTER outlet, two-contact with ground contact • 3 SLAVE outlets with auto switch off the power supply after switch off the receiver powered from MASTER outlet • 2 outlets separate from MASTER outlet
Length of the cable	...	1.45 m
Dimensions	Ø 12 x 40 mm	447 x 55 x 53 mm
Weight	0.002 kg	0.56 kg
Guarantee	2 years	2 years