







	<a href="#">CABLE FOR SOLAR INSTALLATIONS H1Z2Z2-K-1X4.0/BK</a>	<a href="#">CONNECTOR FOR LED STRIPS AD-TL-6499/Z-P/RGBW 12 mm ORNO</a>	<a href="#">TV OR MONITOR MOUNT AX-MAGNUM</a>	<a href="#">ROUTER RG-EG105G-P-V2, 4 PoE REYEE</a>	<a href="#">ROUTER ER-X EdgeMAX UBIQUITI</a>	<a href="#">4-CHANNEL REMOTE CONTROL UREMOTE-BASIC/BLEBOX Wi-Fi</a>
						
	0.92 EUR 0.92 EUR	1.37 EUR 1.37 EUR	16.01 EUR 16.01 EUR	164.89 EUR 164.89 EUR	66.90 EUR 66.90 EUR	29.39 EUR 29.39 EUR
Mounting standard	...	...	VESA max. 600 x 400	...	...	...
Application	...	Works with LED lighting RGBW	...	...	...	...
Processor	...	...	...	...	Dual-Core 880 MHz, MIPS1004Kc	...
Number of power outputs	...	2 pcs	...	...	...	...
Strip width	...	12 mm	...	...	...	...
Screen size range	...	...	32 " ... 65 "	...	...	...
Length of the cable	...	140 mm	...	...	...	...
Bearing capacity	...	...	30 kg	...	...	...
Standards	...	...	...	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, 802.3z, IEEE 802.3af, IEEE 802.3at	IEEE 802.3ad, IEEE 802.1q	...
Distance from mounting surface	...	...	58 mm	...	...	...
"Index of Protection"	...	—	...	...	...	...
Maximal power voltage	...	48 V	...	...	...	...
Inner conductor	4.0 mm <sup>2</sup> - Stranded wire Cu - Tin-plated	...	...	...	...	...
Tilt adjustment	...	...	-15 ° ... 5 °	...	...	...
Wireless	...	...	...	...	...	Wi-Fi, 2.4 GHz - IEEE 802.11g
Horizontal rotation	...	...	—	...	...	...
Rotation in the plane of the screen	...	...	—	...	...	...
Rated voltage	600 V / 1000 V AC 1800 V DC	...	...	...	...	...
Operation range	...	...	...	...	...	≤ 100 m (in open area) ≤ 40 m (internal)
LAN ports	...	...	...	• 3 x LAN & PoE 10/100/1000 Mbps (RJ-45) • 1 x LAN & PoE / WAN 10/100/1000 Mbps (RJ-45)	5 x LAN 10/100/1000 Mbps (RJ-45)	...
Outer coating	Ø 5.0 mm - Non-halogen plastic	...	...	...	...	...
WAN interface	...	...	...	• 1 x WAN x 10/100/1000 Mbps (RJ-45)	configurable	...
LED indicators	...	...	...	Status, Link/Act	Power, LAN	...
DDNS	...	...	...	✓	✓	...
DHCP server	...	...	...	✓	✓	...
Port USB	...	...	...	—	—	...
Firmware update	...	...	...	✓	...	...
Coating color	Black	...	...	...	...	...
Protections	...	...	...	• ACL • IP-MAC Binding • MAC addresses filtering • Support for dynamic ARP mapping and static table • NAT / NAPT • Port Mapping	• NAT network firewall • LAN ACL • Contact/Air (ESD/EMP) : ± 24 kV / ± 24 kV	...
Color	...	White	Black	...	...	Black
Management interface	...	...	...	• Ruijie Cloud Central Management System • Configuration using the Ruijie Reye application • Remote management • Web browser	• Software EdgeOS, Software PC • Remote management • Web browser	...
Mobile phones support	...	...	...	Android: Free application <a href="#">Ruijie Reye</a> iOS (iPhone): Free application <a href="#">Ruijie Reye</a>	...	• The <a href="#">wBox</a> free application on Android • The <a href="#">wBox</a> free application on iOS
Power supply PoE	...	...	...	Power output - LAN ports : PoE (802.3af/at) max. 54 W (total)	Ubiquiti Passive PoE	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Housing	...	Plastic	...	...	Metal	Plastic (ABS)
Main features	<ul style="list-style-type: none"> <li>• UV radiation resistance</li> <li>• Ozone resistance</li> <li>• Hydrolysis resistance</li> <li>• Resistant to oils and aggressive chemicals</li> <li>• Flame resistance (according to VDE 0482-332-2, DIN EN 60332-1)</li> <li>• The insulating layer is made of halogen-free material, which does not produce aggressive fumes during combustion</li> <li>• Increased mechanical strength of the outer coating</li> <li>• Expected lifetime : 25 years</li> </ul>	...	In the kit : Expansion plugs Ø 8 x 50 mm	<ul style="list-style-type: none"> <li>• VPN networks: IPsec VPN, Open VPN, L2TP VPN, PPTP VPN, etc.</li> <li>• Static / dynamic routing</li> <li>• WAN : PPPoE, PPTP, L2TP</li> <li>• DHCP client/server support</li> <li>• Access Control List - ACL package filtering based on source and destination IP addresses</li> <li>• Rate limit</li> <li>• Load balance</li> <li>• NAT</li> <li>• View topology and network status</li> <li>• RESET button</li> </ul>	<ul style="list-style-type: none"> <li>• IEEE 802.1Q VLAN</li> <li>• PPPoE</li> <li>• Static routing</li> <li>• DHCP</li> <li>• IPv6 compliance</li> <li>• IGMP</li> <li>• NAT</li> <li>• VPN networks: IPsec VPN, L2TP VPN, PPTP VPN, Open VPN</li> <li>• Dynamic DNS</li> <li>• Client - Radius support</li> <li>• QoS - mechanisms, which provide the high quality of transmission</li> <li>• Switch is managed via a web browser, command line interface and SNMP, NetFlow, LLDP, NTP, UBNT Discovery Protocol protocols</li> <li>• View topology and network status</li> <li>• RESET button</li> <li>• Possible power supply via Passive PoE via eth4/Poe OUT port - 24 V ("+": 4, 5 pins; "-": 7, 8 pins)</li> <li>• Possibility to mount to the wall</li> </ul>	<ul style="list-style-type: none"> <li>• Number of buttons : 4</li> <li>• 4 independent channels,</li> <li>• 4 groups,</li> <li>• Number of supported devices : 3 / Channel,</li> <li>• Controlling BleBox devices</li> <li>• Order confirmation</li> <li>• LED indication</li> <li>• Bidirectional communication</li> <li>• Transmission encryption</li> <li>• µWiFi technology support</li> <li>• Control possible without Wi-Fi network available</li> </ul>
Power supply	...	...	...	54 V DC / 1.15 A (power adapter included)	<ul style="list-style-type: none"> <li>• 12 V DC / 0.5 A (power adapter included)</li> <li>• Passive PoE 24 V - port eth0/PoE IN</li> </ul>	<ul style="list-style-type: none"> <li>• built-in battery - lithium-polymer</li> <li>• 5 V micro USB (battery charging)</li> <li>• Estimated battery operation time : 2 years</li> </ul>
Power consumption	...	...	...	max. 60 W (at full load)	max. 5 W	...
Operation temp	...	...	...	0 °C ... 40 °C	-10 °C ... 45 °C	-20 ... 50 °C
Permissible relative humidity	...	...	...	10 % ... 90 % (non-condensing)	10 % ... 90 % (non-condensing)	...
Weight	...	0.002 kg	1.27 kg	0.43 kg	0.172 kg	0.028 kg
Dimensions	...	140 x 15 x 5 mm	640 x 420 x 50 mm	207 x 109 x 28 mm	110 x 75 x 22 mm	72 x 39 x 12 mm
Manufacturer / Brand	...	ORNO	...	RUIJIE / REYEE	UBIQUITI	BleBox
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years