




	<a href="#">TV OR MONITOR MOUNT AX-FLEXI-42</a>	<a href="#">EXPANSION PLUG WITH SWING HOOK KH-12/8X120</a>	<a href="#">ACCESS CONTROLLER PR311SE-BK ROGER</a>
			
	77.74 NOK 77.74 NOK	11.28 NOK 11.28 NOK	1269.39 NOK 1269.39 NOK
Cards support	...	...	Unique EM 125kHz
Reading distance of prox-keys	...	...	max. 15 cm
Keyboard built-in	...	...	—
Material	...	Expansion plug - Polypropylene Screw - Steel galvanized	...
Drilling diameter	...	12 mm	...
Mounting standard	VESA 75, 100, 200 x 100, 200	...	...
Communication	...	...	<ul style="list-style-type: none"> <li>• RS-485</li> <li>• RACS (Roger)</li> </ul>
Expansion plug length	...	60 mm	...
Screen size range	13 " ... 42 "	...	...
Selected features of the standalone mode	...	...	<ul style="list-style-type: none"> <li>• 1000 indexed users</li> <li>• Operation with XM-2 I/O extension module (Full Standalone Mode)</li> </ul>
Screw	...	90 mm (L)	...
Bearing capacity	25 kg	...	...
Screw dimensions	...	Ø 8 x 90 mm	...
Distance from mounting surface	56 ... 230 mm from wall	...	...
Color	Black	...	...
Tilt adjustment	-5 ° ... 15 °	...	...
Horizontal rotation	Articulated arm with two swivels in range -90 ° ... 90 ° each	...	...
Rotation in the plane of the screen	—	...	...

Main features	...	...	<ul style="list-style-type: none"> <li>• The ability to add additional reader (bilateral way door control),</li> <li>• 3 programmable input lines NO/NC,</li> <li>• 2 programmable transistor outputs 1A,</li> <li>• One programmable relay output 1.5A/30V,</li> <li>• Door modes (Normal, Locked, Unlocked and Conditionally Unlocked),</li> <li>• Any topology of communication bus,</li> <li>• "Guest" type additional users support defined individually on each controller,</li> <li>• Integration with an alarm system via in/out line ,</li> </ul>
Power supply	...	...	10 ... 15 V DC
Average current consumption	...	...	50 mA
Operation temp	...	...	-25 °C ... 60 °C
Permissible relative humidity	...	...	10 ... 95 % (non-condensing)
Weight	1.15 kg	...	0.18 kg
Dimensions	220 x 220 x (56 ... 230) mm	...	152.5 x 46 x 23 mm (Standard housing stand) 152.5 x 46 x 35 mm (Thicker housing stand)
Manufacturer / Brand	...	...	ROGER
Guarantee	2 years	2 years	3 years