



	SWITCH POE GTX-A1-06-42 4-PORT	ELECTRIC CABLE YDY-5X4.0
		
	54.86 CAD 54.86 CAD	7.27 CAD 7.27 CAD
In section	...	100 m . Price for 1m when buying a whole roll
Inner conductor	...	5 x 4.0 mm ² - Cu wire
LAN ports	<ul style="list-style-type: none"> • 4 x RJ45 (1 x Hi-PoE + 3 x PoE (802.3af/at)), • 2 x RJ45 - Uplink 	...
Rated voltage	...	450 / 750 V
Outer coating	...	Ø 14.5 mm - PVC
Coating color	...	White
Management	—	...
LED diodes	Power, V - VLAN (Port Isolation), S - Extend, PoE, Link/Act	...
Transmission speed	10 / 100 Mbps : 2 x Port LAN - Uplink + 4 x Port LAN & PoE	...
Operation modes	<ul style="list-style-type: none"> • N - Normal - the device operates as normal PoE switch • V - VLAN (Port Isolation) - 1 ... 4 ports are isolated from each other and separately work with the 5, 6 ports • S - Extend - Range : 250 m @ 10 Mbps 	...
Maximal output power	<ul style="list-style-type: none"> • 60 W / port Hi-PoE - Port 1 • 30 W / port PoE - 2 ... 4 ports 	...
Maximal total power	65 W	...
MAC addresses table	1k	...

Main features	<ul style="list-style-type: none"> • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Full Duplex: IEEE802.3x, Half Duplex: Back Pressure • Auto-learning and Auto-aging functions support for MAC addresses • PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • MTBF (Mean Time Between Faults) : 50000 h 	...
Certificates	CE, FCC Class B	...
Protections	Overvoltage \pm 3 kV	...
Power supply	100 ... 265 V AC	...
Operation temp	-10 °C ... 55 °C	...
Weight	0.6 kg	...
Dimensions	190 x 130 x 35 mm	...
Guarantee	2 years	2 years