


	KIT ZSW-02 SUPLA ZAMEL	DUAL SMART LED LIGHTING CONTROLLER ATLO-SW2-TUYA Wi-Fi, Tuya Smart	CONNECTOR FOR LED STRIPS AD-TL-6499/Z/L 8 mm ORNO
			
	376.49 EUR 376.49 EUR	11.40 EUR 11.40 EUR	0.75 EUR 0.75 EUR
Number of channels	...	2	...
Strip width	8 mm
Support	SUPLA
Power supply	...	100 ... 240 V AC, 50 / 60 Hz	...
Maximal power voltage	48 V
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	<ul style="list-style-type: none"> • Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n • Bluetooth 	...
Radio communication range	...	< 100 m (open area)	...
Mobile phones support	<ul style="list-style-type: none"> • The SUPLA free application on Android • The SUPLA free application on iOS 	<ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS 	...
Manufacturer / Brand	ZAMEL	...	ORNO
Main features	<ul style="list-style-type: none"> • Control from a Web browser, • Local control by physical button, • schedule, • timer, • remote access, • voice control, • Possibility to manually program scenarios from the built-in API 	<ul style="list-style-type: none"> • Local control by physical button , Tuya Smart : • schedule, • timer, • Setting scenarios by different events, • remote access, • voice control , 	...
Housing	Plastic	Plastic	...
Color	Green	White	White
Power voltage	230 V AC
Relay maximal load	2 x 5 A @ 250 V AC
Guarantee	2 years	2 years	2 years
Number of pins	2 x NO
Number of elements	7 3 3 1

Application	roller shutters, roof windows, awnings, drop-down screens, curtains Lighting control, switching devices on/off Works with LED lighting - (RGB) 12-24V LED strips	switching devices on/off	Works with LED lighting
Rated voltage	230 V AC 12 ... 24 V DC
Maximal total load	1250 VA 140 W	2 x 150 W	...
Total maximal current	5 A 6 A (2 A / Channel)	2 x 5 A	...
Maximal outputs load	350 W • 750 W (single output) - light bulbs and halogen lamps • 250 W (single output) - CFL fluorescent lamps • 60 W (single output) - LED bulbs LED RGB 12 V : 5 m - 70 W LED RGB 24 V : 10 m - 140 W
Number of inputs	2 pcs 2 1	2	...
Number of outputs	1 pcs (Motor) 3	2	...
Connector type	screw terminals screw terminals screw terminals screw terminals	screw terminals	...
"Index of Protection"	IP20 IP20 IP20	IP20	—
Operation temp	-10 °C ... 55 °C -10 °C ... 55 °C -20 °C ... 50 °C	-10 °C ... 40 °C	...
Weight	0.407 kg 0.030 kg 0.04 kg 0.030 kg	0.03 kg	0.002 kg

Dimensions	47 x 47 x 20 mm 47 x 47 x 20 mm 47 x 47 x 20 mm	43 x 39 x 22 mm	17 x 17 mm
------------	---	-----------------	------------



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00