




	MULTI-SOCKET PLUG LE-49400 3680 W LEGRAND	CABLE PAIR DETECTOR WITH RJ-45 CABLE TESTER UT-682 UNI-T	AHD, HD-CVI, HD-TVI, PAL CAMERA BCS-EA45VR4(H2) - 5 Mpx 3.3 ... 12 mm	BATTERY 12V/5AH-MWS
				
	5.79 EUR 5.79 EUR	29.66 EUR 29.66 EUR	51.82 EUR 51.82 EUR	9.55 EUR 9.55 EUR
Battery capacity	5.0 Ah
Rated voltage	230 V / 50 Hz	12 V
Maximal total load	3680 W
Battery charging current	max. 1.5 A
Standard	AHD / HD-CVI / HD-TVI / CVBS	...
Battery type	Maintenance-free AGM (Absorbent Glass Mat) battery
Tested cables	...	UTP, FTP, YTKSY - RJ45 (8P8C), RJ11 (6P4C)
Connector	T1 type
Total maximal current	16 A (6 A socket)
Number of outlets	4 pcs
Battery lifetime	3 ... 5 years
Socket type	2P (flat)
Plug type	CEE 7/4 (Schuko)
Main features	...	<ul style="list-style-type: none"> • Test for the presence of a short circuit, open circuit • Polarity indicator for telephone wire pairs : \pm (5V ... 52V) • The maximum length of the telephone line : 3000 m • Optical - sound signaling • Low battery indicator
Grounding	—
Operation temp	...	0 °C ... 40 °C
Permissible relative humidity	...	20 % ... 75 %
Resolution	2704 x 1950 - 5 Mpx @ AHD / HD-TVI @ 20 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-TVI / HD-CVI @ 25 fps , 1920 x 1080 - 1080p @ AHD / HD-TVI / HD-CVI @ 25 fps 960 x 576 - 960H @ CVBS	...
Sensor	1/2.5 " CMOS	...
Lens	3.3 ... 12 mm	...
View angle	120 ° ... 38 °	...
Range of IR illumination	40 m	...
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...
Audio	—	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

OSD menu	✓	...
Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • Auto White Balance • AGC • Day/night mode • ICR - Movable InfraRed filter 	...
Power supply	...	2 x 9V, type 6F22 battery (included)	12 V DC / 670 mA	...
Power consumption	< 8 W	...
Housing	Plastic	...	Dome, Metal	...
Color	White / Light gray	...	White	...
"Index of Protection"	IP66	...
Mechanical protection class	—	...
Operation temp	-20 °C ... 60 °C	...
Weight	0.104 kg	<ul style="list-style-type: none"> • 0.11 kg - Transmitter • 0.14 kg - Receiver 	0.559 kg	1.36 kg
Dimensions	96 x 74 x 72 mm	<ul style="list-style-type: none"> • 125 x 48 x 29 mm - Transmitter • 194 x 50 x 30 - Receiver 	Ø 119 x 98 mm	90 x 107 x 70 mm
Supported languages	Polish, English	...
Manufacturer / Brand	LEGRAND	UNI-T	BCS UNIVERSAL	...
Guarantee	2 years	2 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00