



	<a href="#">KEYPAD FOR ALARM CONTROL PANEL INT-KLCD5-GR SATEL</a>	<a href="#">POWER DISTRIBUTION UNIT ACAR-XPROTECTOR</a>	<a href="#">SWITCH POE SPS-2P/1 3-PORT</a>	<a href="#">SWITCH POE XPOE-6-11-OF 5-PORT ATTE</a>	<a href="#">SWITCH POE IP-5-11-E 5-PORT ATTE</a>
					
	114.21 USD 114.21 USD	21.81 USD 21.81 USD	35.30 USD 35.30 USD	59.44 USD 59.44 USD	137.32 USD 137.32 USD
Support	INTEGRA	...	...	...	...
Rated voltage	...	230 V AC / 50 Hz	...	...	...
Total maximal current	...	10 A	...	...	...
LAN ports	...	...	3 x RJ45 ( 2 x PoE (802.3af) )	• 1 x RJ45 10/100 Base-T - Uplink • 5 x RJ45 10/100 Base-T, PoE 802.3af/at / Passive PoE	• 1 x RJ45 10/100 Base-T - Uplink • 5 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE
Maximal total load	...	2300 W	...	...	...
Response time	...	< 25 ns	...	...	...
Number of outlets	...	5 grounded outlets 10A/250V	...	...	...
Main features	<ul style="list-style-type: none"> <li>• Green backlight of the keys</li> <li>• LEDs indicating device operation state</li> <li>• Alarms: keypad hold-down PANIC, FIRE and AUX</li> <li>• Buzzer for acoustic signaling of some system events</li> <li>• 2 Inputs</li> <li>• Panel communication loss indication</li> <li>• RS-232 port allows to programming using the PC with GUARDX software installed</li> <li>• Microswitch as tamper contact</li> </ul>	...	...	...	...
Management	...	...	—	—	—
Current consumption	max. 151 mA	...	...	...	...
Automatic delayed fuse	...	10 A / 250 V	...	...	...
Leak current	...	< 0.5 mA	...	...	...
LED diodes	...	...	Power, PoE, Link/Act	Power, LAN	Power, LAN
Nominal voltage of surge suppressor	...	250 V / 50 Hz	...	...	...
Protection level of surge suppressor	...	≤ 1.3 kV (L/N)	...	...	...
Transmission speed	...	...	10 / 100 Mbps : 1 Port LAN + 2 LAN & PoE ports	10 / 100 Mbps : 1 Port LAN + 5 LAN & PoE ports	10 / 100 Mbps : 1 Port LAN + 5 LAN & PoE ports
Nominal stroke current	...	1 kA (L/N) - (8/20μs)	...	...	...
MAC addresses table	...	...	1k	...	...
Certificates	...	...	CE	...	...
Switch	...	two-way, with light indication	...	...	...
Maximum stroke current	...	4.5 kA (L/N) - (8/20μs)	...	...	...
Length of the cable	...	1.45 m	...	...	...
Housing	...	Plastic - non-flammable	...	...	...
Operation temp	-10 °C ... 55 °C	...	-20 °C ... 70 °C	...	...
Maximal output power	...	...	15.4 W / port PoE	• 40 W @ Passive PoE - 1 ... 4 ports, • 70 W @ Passive PoE - Port 5, • 30 W @ PoE (802.3af/at) - 1 ... 5 ports	• 40 W @ Passive PoE - 1 ... 4 ports, • 70 W @ Passive PoE - Port 5, • 30 W @ PoE (802.3af/at) - 1 ... 5 ports

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Maximal total power	...	...	36 W	<ul style="list-style-type: none"> <li>• 70 W @ Power supply PoE,</li> <li>• 230 W @ Power supply 48V DC</li> </ul>	96 W
Operation modes	...	...	...	<ul style="list-style-type: none"> <li>• Standard : 100 m @ 10/100 Mb/s - 1 ... 6 ports</li> <li>• Long Range : 280 m @ 10 Mb/s - 1 ... 4 ports ; 100 m @ 10/100 Mb/s - 5, 6 ports</li> </ul>	<ul style="list-style-type: none"> <li>• Normal : 100 m @ 10/100 Mb/s - 1 ... 5 ports</li> <li>• Long Range : 280 m @ 10 Mb/s - 1 ... 4 ports ; 100 m @ 10/100 Mb/s - Port 5</li> <li>• Port LAN 6 - Uplink</li> </ul>
Main features	...	...	...	<ul style="list-style-type: none"> <li>• Possible power supply via Passive PoE via LAN 5 port</li> <li>• Possible cascading device connection (power transmission between devices using Passive PoE via LAN 5 port)</li> <li>• The LAN 5 (PoE IN/OUT) port can be used to power PoE devices as well as to draw power from other devices</li> <li>• The output PoE voltage is equal to the input voltage</li> <li>• The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 5 ports</li> </ul>	<ul style="list-style-type: none"> <li>• Possible cascading device connection (power transmission between devices using Passive PoE via LAN 5 port)</li> <li>• The output PoE voltage is equal to the input voltage</li> <li>• The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 5 ports</li> <li>• The modular design streamlines service tasks and enables quick and easy system expansion</li> <li>• The raster system of module assembly facilitates the expansion of the device by further modules</li> </ul>
Power supply	12 V DC	...	52 V DC / 1.25 A (power adapter included)	<ul style="list-style-type: none"> <li>• 10 ... 56 V DC ( cable terminals )</li> <li>• 10 ... 56 V DC ( Passive PoE )</li> </ul>	230 V AC - cable terminals
Weight	0.14 kg	0.51 kg	0.13 kg	0.05 kg	1.4 kg
Dimensions	114 x 94 x 24 mm	365 x 65 x 52 mm	96 x 71 x 26 mm	88 x 68 x 20 mm	255 x 205 x 95 mm
Manufacturer / Brand	SATEL	...	...	ATTE	ATTE
Guarantee	2 years	2 years	2 years	3 years	3 years