





	IP CAMERA IPC3612LE-ADF28KMC-WL-BLACK ColorHunter - 1080p 2.8 mm UNIVIEW	ACOUSTIC GLASSBREAK DETECTOR TESTER TESTER-INDIGO SATEL	PLUG-IN MODULE FOR OVERVOLTAGE LIMITER LE-412302 1+2 TYPE 50 kA LEGRAND	STEEL CABLE LS-4/200
				
	150.05 USD 150.05 USD	84.99 USD 84.99 USD	51.66 USD 51.66 USD	0.76 USD 0.76 USD
Standard	TCP/IP
Type of imitated sounds	...	Plate, laminated, tempered glass breaking
Rated voltage	230 / 400 V AC, 50 / 60 Hz	...
Sensor	1/2.8 " Progressive Scan CMOS
Matrix size	2.1 Mpx
In section	200 m . Price for 1m when buying a whole roll
Maximal voltage	320 V AC, 50 / 60 Hz	...
Material	Steel
External diameter	Ø 4 mm
Inner diameter	—
Class	1+2 type (Class B+C)	...
Tensile strength	830 kg
Resolution	1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	2.8 mm @ F1.6
Protection level Up	1.2 kV @ 10/350 µs (T1) 1.7 kV @ 8/20 µs (T2)	...
View angle	• 107 ° (manufacturer data) • 100 ° (our tests result)
White light LED illuminator range	30 m
Nominal discharge current	8 kA @ 10/350 µs (T1) 20 kA @ 8/20 µs (T2)	...
Range of IR illumination	30 m
S/N ratio	> 52 dB
Maximum stroke current	50 kA @ 8/20 µs (T2)	...
RS-485 interface	—
Operation state indication	✓	...
Memory card slot	Micro SD memory cards up to 128GB support (possible local recording)
Main features	Varistor	...
Image compression method	Ultra 265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	—
Audio	• Microphone built-in, • Speaker built-in • Bi-directional audio streaming support • Audio transmission via network • Audio detection
Main stream frame rate	25 fps @ 4 Mpx
Network interface	10/100 Base-TX (RJ-45)
Network protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, SNMP
WEB Server	Built-in

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Max. number of on-line users	32
ONVIF	✓
Mobile phones support	Access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView
Default IP address	DHCP or 192.168.1.13
Default admin user / password	admin / 123456
Web browser access ports	80, 554
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	80
Port ONVIF	80
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream
Main features	<ul style="list-style-type: none"> • ColorHunter - colorful night mode • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • BLC/HLC - Back Light / High Light Compensation • Auto White Balance • Day/night mode • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Possibility to change the resolution, quality and bit rate • Sharpness - sharper image outlines • Image rotation and mirror • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • Privacy zones - max. 4 • Motion Detection • Intelligent image analysis : crossing the line (tripwire), intrusion (human silhouette)
Power supply	• PoE (802.3af), • 12 V DC / 670 mA	9 V alkaline battery 6LR61 (not included)
Power consumption	≤ 8 W
Housing	Dome, Metal + Plastic	...	Plastic	...
Color	Black
"Index of Protection"	IP67
Vandal-proof	—
Operation temp	-30 °C ... 60 °C
Weight	0.35 kg	0.11 kg	0.098 kg	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Dimensions	Ø 118 x 95 mm	196 x 69 x 33 mm	62 x 54 x 17 mm	...
Supported languages	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian
Manufacturer / Brand	UNIVIEW	SATEL	LEGRAND	...
Guarantee	3 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00