



| | RUBBER MAT MB-GUM/50 | SWITCH POE DS-3E1106HP-EI 4-PORT Hikvision | ELECTRIC STRIKE R5-12.13 REVERSIBLE |
|---|---|--|---|
| |  |  |  |
| | 47.03 DKK 47.03 DKK | 506.05 DKK 506.05 DKK | 159.66 DKK 159.66 DKK |
| Rated voltage | ... | ... | 10 V ± 2 V DC |
| Current consumption | ... | ... | 280 mA DC |
| Color | Black | ... | ... |
| Application | <ul style="list-style-type: none"> • Area covering, • Soundproofing | ... | right-side door / left-side door |
| Ratched lock | ... | ... | — |
| Material | SBR granulate + polyurethane binder | ... | ... |
| Memory function | ... | ... | — |
| Reverse action | ... | ... | ✓ |
| Clearance adjustment | ... | ... | ✓ |
| Allowable thrust on the door at ratchet release | ... | ... | 30 N |
| Allowable load of the door impacting the lock | ... | ... | 3000 N |
| Allowable uninterrupted operation time | ... | ... | unlimited |
| LAN ports | ... | <ul style="list-style-type: none"> • 4 x RJ45 10/100 Base-TX (1 x Hi-PoE (802.3af/at/bt) + 3 x PoE (802.3af/at)), • 2 x RJ45 10/100 Base-TX - Uplink | ... |
| Transmission speed | ... | <ul style="list-style-type: none"> • 10 / 100 Mbps - 4 LAN & PoE ports, • 10 / 100 Mbps - 2 Uplink ports | ... |
| Maximal output power | ... | <ul style="list-style-type: none"> • 60 W / port Hi-PoE / PoE 802.3bt - Port 1 • 30 W / port PoE 802.3af/at - 2 ... 4 ports | ... |
| Maximal total power | ... | 60 W | ... |
| MAC addresses table | ... | 2k | ... |
| Management | ... | ✓ | ... |
| Default IP address | ... | 192.168.1.64 | ... |
| Default admin user / password | ... | admin / - | ... |

| | | | |
|----------------------|---|--|-----------------|
| Operation modes | ... | <ul style="list-style-type: none"> • Extend On : 300 m, 10 Mbps • Extend Off : 100 m, 100 Mbps | ... |
| Main features | <ul style="list-style-type: none"> • Rough structure • Granule fraction : 0.5 ... 4 mm • Insulation • High fatigue strength of the material • Weatherproof • Very easy and quick assembly | <ul style="list-style-type: none"> • The device supports 8-pin power supply - wires : 1-2(-), 3-6(+), 4-5(+), 7-8(-) • Endspan mode support - wires : 1-2(-), 3-6(+) • Midspan mode support - wires : 4-5(+), 7-8(-) • High priority ports : 1, 2 • Configuration and management from the iVMS-4200 application • View topology and network status • Data Flow Control • Alarm notifications • Remote update of software • System logs • Possibility to mount to the wall | ... |
| LED diodes | ... | Power, Link/Act, PoE, PoE Max, 5 Uplink, 6 Uplink | ... |
| Certificates | ... | CE, FCC, RoHS | ... |
| Housing | ... | Desktop, Metal | ... |
| Protections | ... | Overvoltage 6 kV - PoE ports | ... |
| Power supply | ... | 48 V DC / 1.35 A (power adapter included) | ... |
| Power consumption | ... | max. 65 W | ... |
| Operation temp | ... | -10 °C ... 55 °C | ... |
| Weight | 2.4 kg | 0.24 kg | 0.13 kg |
| Dimensions | 500 x 500 x 10 mm | 145 x 69 x 26 mm | 18 x 32 x 68 mm |
| Manufacturer / Brand | ... | Hikvision | ... |
| SAP Code | ... | 301802043 | ... |
| Guarantee | ... | 3 years | 2 years |