



	ACCESS POINT 4G+ LTE Cat. 6 +ROUTER ARCHER-MR600 Wi-Fi 2.4 GHz, 5 GHz 867 Mbps + 300 Mbps TP-LINK	EXPANSION PLUG JPK-12X300/M5 EBOLT
		
	148.64 EUR 148.64 EUR	2.83 EUR 2.83 EUR
Frequency range	2.4 GHz , 5 GHz	...
Material	...	<ul style="list-style-type: none"> • Expansion plug - Polypropylene • Screw - Steel galvanized • mounting screw - Steel galvanized
Drilling diameter	...	12 mm
Expansion plug length	...	295 mm
Antenna type	WiFi - built-in , 2 x 4G LTE	...
Screw dimensions	...	Ø 8 x 300 mm, Internal thread M5
Standards	<ul style="list-style-type: none"> • IEEE 802.11 b/g/n, • IEEE 802.11 a/n/ac 	...
Screw	...	Ø 5 x 16 mm
Application	...	for Styrofoam 220 mm
Baud rates	<ul style="list-style-type: none"> • 5 GHz : 867 Mbps (max) + 2.4 GHz : 300 Mbps (max) • LTE : 300 Mbps 	...
LAN ports	<ul style="list-style-type: none"> • 1 x 10/100/1000 Mbps - LAN/WAN • 3 x 10/100/1000 Mbps - LAN 	...
Receiver sensitivity	5 GHz : <ul style="list-style-type: none"> • 11a 54M: -74dBm • 11ac HT20: -66 dBm • 11ac HT40: -63 dBm • 11ac HT80 : -59 dBm • 11n HT20: -73dBm • 11n HT40: -70dBm 2.4 GHz : <ul style="list-style-type: none"> • 11g 54M: -74dBm • 11n HT20: -72 dBm • 11n HT40: -69 dBm 	...
LTE	✓	...
QSS	—	...
WDS	✓	...

Transmitter power	max. 23 dBm	...
Main features	<ul style="list-style-type: none"> • IP-layer bandwidth control mechanism • Local, remote or via TP-Link Cloud management • Support for TP-Link OneMesh™ technology • SIM socket • WPS/RESET button 	...
Power supply	12 V DC / 1.5 A (power adapter included)	...
Operation temp	0 °C ... 40 °C	...
Permissible relative humidity	95 % (non-condensing)	...
Weight	0.478 kg	...
Dimensions	230 x 163 x 37 mm	...
Manufacturer / Brand	TP-LINK	EBOLT
Guarantee	3 years	2 years

