





	IP CAMERA APTI-52VA2-28WP - 5 Mpx 2.8 mm	SMART SWITCH SWITCHBOX-DIN/BLEBOX Wi-Fi, 230 V AC	POWER DISTRIBUTION UNIT LE-049470 (3 OUTLETS) 1.5 m LEGRAND	PROTECTIVE HOOD FOR MOTION DETECTORS HOOD-C-GY SATEL	TV OR MONITOR MOUNT AX-FLEXI-APOLLO	SWITCHING ADAPTER PS65-15-DIN ACO
						
	74.85 EUR 74.85 EUR	47.20 EUR 47.20 EUR	9.71 EUR 9.71 EUR	7.53 EUR 7.53 EUR	14.53 EUR 14.53 EUR	59.24 EUR 59.24 EUR
Application	...	switching devices on/off	...	OPAL-GY, OPAL-PLUS-GY, OPAL-PRO-GY	...	ACO Video Doorphones
Standard	TCP/IP	...	...	...	...	...
Assembly	...	...	...	"Click"-type closing	...	...
Rated voltage	...	230 V AC	230 V AC / 50 Hz	...	...	...
Sensor	1/2.5 " Progressive Scan CMOS	...	...	...	...	...
Adapter type	...	...	...	...	...	Switching
Matrix size	5 Mpx	...	...	...	...	...
Maximal total load	...	3680 W (resistance load) / 500 W (inductive or capacitive load)	3680 W	...	...	...
Power voltage	...	...	...	...	...	100 ... 240 V AC
Total maximal current	...	16 A	16 A	...	...	...
Number of outlets	...	...	3 grounded outlets 16A/250V CEE 7/5	...	...	...
Output voltage	...	...	...	...	...	15 V DC
Fuse	...	...	—	...	...	...
Number of inputs	...	2	...	...	...	...
Output voltage adjustment	...	...	...	...	...	—
Mounting standard	...	...	...	...	VESA 50, 75, 100, 200 x 100, 200	...
Switch	...	...	—	...	...	...
Maximal load	...	...	...	...	...	4 A
Wire gauge	...	...	3 x 1.0 mm <sup>2</sup>	...	...	...
Connector type	...	screw terminals	...	...	...	...
Output power	...	...	...	...	...	65 W
Screen size range	...	...	...	...	17 " ... 42 "	...
Length of the cable	...	...	1.5 m	...	...	...
Number of outputs	...	1	...	...	...	2 pcs
Bearing capacity	...	...	...	...	35 kg	...
Efficiency	...	...	...	...	...	≤ 91 %
Housing type	...	...	...	...	...	DIN
Distance from mounting surface	...	...	...	...	89 ... 466 mm	...
Wireless	...	Wi-Fi, 2.4 GHz - IEEE 802.11g	...	...	...	...
Protections	...	...	...	...	...	• Short-circuit • Overload • Overheat
Tilt adjustment	...	...	...	...	-15 ° ... 15 °	...
Resolution	2592 x 1944 - 5 Mpx , 2560 x 1920 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p	...	...	...	...	...
Lens	2.8 mm	...	...	...	...	...
Horizontal rotation	...	...	...	...	Articulated arm with two swivels in range -90 ° ... 90 ° each	...
Rotation in the plane of the screen	...	...	...	...	—	...
View angle	• 99 ° (manufacturer data) • 100 ° (our tests result)	...	...	...	...	...
Range of IR illumination	20 m	...	...	...	...	...
Memory card slot	—	...	...	...	...	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...	...	...	...	...
Alarm inputs / outputs	—	...	...	...	...	...
Audio	• Microphone built-in • Audio transmission via network	...	...	...	...	...
Main stream frame rate	max. 25 fps @ 5 Mpx	...	...	...	...	...
Network interface	10/100 Base-T (RJ-45)	...	...	...	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	...	<ul style="list-style-type: none"> <li>• Local control by physical button,</li> <li>• schedule,</li> <li>• sunrise and sunset mode,</li> <li>• timer,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• The ability to set the default status of the device after a power failure,</li> <li>• Energy consumption metering,</li> <li>• Power measurement,</li> <li>• Charts and measurement history</li> <li>• µWiFi technology support</li> <li>• Illuminated, color front panel with an additional control button</li> </ul>	...	...	...	...
Operation temp	...	-20 °C ... 50 °C	...	...	...	...
Network protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP, UDP	...	...	...	...	...
WEB Server	Built-in	...	...	...	...	...
Max. number of on-line users	10	...	...	...	...	...
ONVIF	2.4	...	...	...	...	...
Main features	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• Flicker Control - The technology eliminates the tiring eyes flickering image effect</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• ICR - Movable InfraRed filter</li> <li>• Motion Detection</li> <li>• Privacy zones - max. 3</li> <li>• Mirror - Mirror image</li> <li>• Day/Night mode - configurable</li> <li>• Sharpness - sharper image outlines</li> </ul>	...	...	...	...	...
Mobile phones support	<ul style="list-style-type: none"> <li>Port no.: 80 or access by a cloud (P2P)</li> <li>• Android: Free application <a href="#">BitVision</a></li> <li>• iOS (iPhone): Free application <a href="#">BitVision</a></li> </ul>	<ul style="list-style-type: none"> <li>• The <a href="#">wBox</a> free application on Android</li> <li>• The <a href="#">wBox</a> free application on iOS</li> </ul>	...	...	...	...
Default IP address	192.168.1.168	...	...	...	...	...
Default admin user / password	admin / admin The administrator password should be set at the first start	...	...	...	...	...
Web browser access ports	80	...	...	...	...	...
PC client access ports	80	...	...	...	...	...
Mobile client access ports	80	...	...	...	...	...
Port ONVIF	80	...	...	...	...	...
RTSP URL	<ul style="list-style-type: none"> <li>rtsp://user:password@ip_address:80/0 - Main stream</li> <li>rtsp://user:password@ip_address:80/1 - Sub stream</li> </ul>	...	...	...	...	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 360 mA</li> </ul>	...	...	...	...	...
Power consumption	≤ 4.4 W	...	...	...	...	...
Housing	Dome, Metal	Plastic (ABS), DIN, TS-35 rail mounting	Plastic	...	...	...
Color	White	White	White / Light gray	Gray	Black	...
"Index of Protection"	IP67	IP20	...	...	...	...
Operation temp	-20 °C ... 60 °C	...	...	...	...	...
Weight	0.31 kg	0.07 kg	0.29 kg	0.036 kg	1.83 kg	0.22 kg
Dimensions	Ø 93 x 74 mm	90 x 17.5 x 65 mm	165 x 53 x 38 mm	89 x 84 x 81 mm	220 x 300 x (89 ... 466) mm	70 x 91 x 59 mm
Supported languages	Polish, English, Bulgarian, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian	...	...	...	...	...
Manufacturer / Brand	APTI	BleBox	LEGRAND	SATEL	...	ACO
Guarantee	2 years	2 years	2 years	2 years	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00