



| | | |
|----------------------|--|---|
| | ACCESS POINT 4G LTE +ROUTER TL-MR100 2.4 GHz 300 Mbps TP-LINK | PLASTIC CLEANER PLASTIC-CLEANER/400 SPRAY / FOAM 400 ml AG TERMOPASTY |
| |  |  |
| | 62.77 EUR 62.77 EUR | 3.43 EUR 3.43 EUR |
| Frequency range | 2.4 GHz | ... |
| Package | ... | Spray / Foam 400 ml |
| Application | ... | Removal of greasy dirt from plastic surfaces |
| Antenna type | WiFi embedded , 2 x 4G LTE - 2 x SMA socket - Possibility to connect the wire antenna | ... |
| Standards | IEEE 802.11 b/g/n | ... |
| Baud rates | 11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 150 Mbps | ... |
| LAN ports | • 1 x 10/100 Mbps - LAN/WAN • 1 x 10/100 Mbps - LAN | ... |
| Receiver sensitivity | • 11g 54M : -74 dBm • 11n HT20 : -71 dBm • 11n HT40 : -68 dBm | ... |
| Transmitter power | < 20 dBm | ... |
| LED indicators | Power, WAN, WLAN, LAN, GSM | ... |
| Network type | • 4G : FDD-LTE B1/B3/B5/B7/B8/B20 - 2100 / 1800 / 850 / 2600 / 900 / 800 MHz • 4G : TDD-LTE B38/B40/B41 - 2600 / 2300 / 2500 MHz • 3G : HSPA/UMTS B1/B5/B8 - 2100 / 850 / 900 MHz | ... |
| LTE | ✓ | ... |
| QSS | — | ... |
| WDS | — | ... |
| DDNS | • DynDNS • No-IP | ... |
| DHCP server | ✓ | ... |
| Firmware update | ✓ | ... |

| | | |
|-------------------------------|---|--|
| Protections | <ul style="list-style-type: none"> • WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK • SPI network firewall • IP-MAC Binding | ... |
| Management interface | Web browser | ... |
| Operation modes | <ul style="list-style-type: none"> • Router, • Router 4G LTE | ... |
| Main features | <ul style="list-style-type: none"> • Number of users - max. 32 • SIM socket - The nanoSIM cards support • WPS/RESET button • Enable/disable wireless network • WMM (Wi-Fi Multimedia) • Wireless Network Schedule • Wireless transmission statistics • The failover function enabling automatic switching between 4G/WAN interface in the case of an Internet network connection loss • Static / dynamic routing • PPTP • L2TP • Remote management • DHCP client list • Port forwarding : UPnP, DMZ • Guest Network - a separate and secure network for guests | The agent, after being applied to the surface, takes the form of a foam that facilitates spreading |
| Power supply | 9 V DC / 0.85 A (power adapter included) | ... |
| Operation temp | 0 °C ... 40 °C | ... |
| Permissible relative humidity | 10 % ... 90 % (non-condensing) | ... |
| Weight | 0.184 kg | 0.46 kg |
| Dimensions | 155 x 114 x 34 mm | Ø 66 x 200 mm |
| Manufacturer / Brand | TP-LINK | AG TERMOPASTY |
| Guarantee | 3 years | ... |