




	EXPANSION PLUG KW-10/5X80 KLIMAS	FLUSH BOX E-3700 SIMET	IP CAMERA DS-2CD1047G2H-LIU(2.8MM)PL ColorVu - 3.7 Mpx Hikvision
			
	0.12 GBP 0.12 GBP	1.66 GBP 1.66 GBP	165.57 GBP 165.57 GBP
Standard	IP
Number of sections	...	1	...
Material	<ul style="list-style-type: none"> Expansion plug, Polypropylene Screw, Steel galvanized
Drilling diameter	10 mm
Expansion plug length	50 mm
Resolution	2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p
Screw dimensions	Ø 5 x 80 mm, PZ-2
Sensor	1/3 " Progressive Scan CMOS
Lens	2.8 mm
Application	<ul style="list-style-type: none"> Concrete Solid clay brick Solid sand-lime brick
View angle	115 °
White light LED illuminator range	30 m
Main features	...	<ul style="list-style-type: none"> Flush-mounted, deep, for hollow walls, with flexible membranes flammability index : 850 °C 2 fixing points 2 Mounting screws, 2 special screws with holders to fastening to the wall - included 	...
Range of IR illumination	30 m
Material	...	Non-halogen plastic	...
Memory card slot	—
Mounting holes distance	...	60 mm	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	—
Audio	<ul style="list-style-type: none"> Microphone built-in, Audio transmission via network Compliance with the AAC standard
Main stream frame rate	20 fps @ 3.7 Mpx
Interface	10/100 Base-T (RJ-45)
WEB Server	Built-in
Max. number of on-line users	6
ONVIF	—

Main features	<ul style="list-style-type: none"> • Smart Hybrid Light / ColorVu technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • SVC (Scalable Video Coding) - technology enabling the transfer of several sub-streams of different quality within one stream • Possibility to change the resolution, quality and bit rate • Horizontal mirror image • Smart motion detection (with recognizing people and vehicles) • Configurable Privacy Zones • Sharpness - sharper image outlines • video tampering • Filtering of false alarms based on the recognition of persons and vehicles
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default IP address	192.168.1.64
Default admin user / password	admin / - The administrator password should be set at the first start
Web browser access ports	80
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	8000
Port ONVIF	80
RTSP URL	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 500 mA
Power consumption	<ul style="list-style-type: none"> • ≤ 7.5 W @ PoE • ≤ 6 W @ 12 V DC
Housing	Compact, Metal + Plastic
Color	...	Orange	White
"Index of Protection"	...	IP30	IP67
Mechanical protection class	—
Operation temp	-30 °C ... 60 °C
Weight	...	0.026 kg	0.3 kg
Dimensions	...	Ø 70 x 60 mm	Ø 70 x 173 mm
Supported languages	Polish
Manufacturer / Brand	KLIMAS	SIMET	Hikvision
SAP Code	311327305
Guarantee	2 years	2 years	3 years