



	DUAL TECHNOLOGY DETECTOR MICROWAVE + PIR SLIM-DUAL-PRO SATEL	VOLTAGE DISTRIBUTION PANEL A19-TS-35/PD-3U
		
	26761.90 HUF 26761.90 HUF	16382.86 HUF 16382.86 HUF
Application	Indoor	...
Width	...	19 "
Pyroelectric sensor	quadruple	...
Height	...	3 U
Sensor type	Passive Infra Red (PIR) and microwave (MW)	...
Material	...	Steel - powder painted
Recommended installation height	2.4 m	...
Range	max. 20 x 24 m	...
"Index of Protection"	...	IP20
Application	...	RACK 19"
Detection angle	90 °	...
Sensitivity adjustment	Separate, smooth sensitivity adjustment for each sensor	...
Alarm output	NC, 2EOL / NC - Set with jumpers	...
Tamper output	✓	...
LED indication	Remote on/off of the LED indicator and choice of lighting color (7 colors available)	...
Microwave frequency band	24.125 GHz	...
Pet immunity	—	...
Antimask feature	✓	...
Alarm time	2 s	...
Maximal outputs load	<ul style="list-style-type: none"> • 40 mA / 24 V DC - Relay output • 40 mA / 24 V DC - Antimasking output • 40 mA / 24 V DC - Tamper 	...
Digital temperature compensation	✓	...
Target speed range	0.2 ... 3 m/s	...
Protection class (Grade)	EN 50131-2-4, Grade 3	...
Environmental class EN 50130-5	II	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Power supply	12 V DC / 85 mA (max)	...
Main features	<ul style="list-style-type: none"> • EN 50130-4, EN50130-5, EN 50131-1, EN 50131-2-2 • digital detection algorithm with temperature compensation for high immunity to false alarms and repeatability of parameters • Tamper detection - opening the enclosure, removing from mounting surface • Remote management • Built-in parametric resistors 2EOL: 2 x 1.1kΩ, 2 x 4.7 kΩ, 2 x 5.6 kΩ • Creep zone control • Remote controlled (not included) 	<ul style="list-style-type: none"> • TH-35 rail • Corrosion resistance • Possibility to mount of 24 fuses, 1 S wide • 6-point fixing to the front RACK rails • 6 pcs. of M6 screws with cage nuts included • The enclosure features labeling field 420x20 mm
Operation temp	-10 °C ... 55 °C	-10 °C ... 40 °C
Color	White	Black (RAL 9005)
Weight	0.11 kg	2.06 kg
Dimensions	137 x 62 x 42 mm	445 x 125 x 55 mm Internal dimensions 481 x 132 x 135 mm External dimensions
Manufacturer / Brand	SATEL	PULSAR
Guarantee	5 years	2 years