

	<a href="#">VIDEO SEPARATOR SV-1000/4-G</a>	<a href="#">POWER DISTRIBUTION UNIT ACAR-P7 (5 + 2 OUTLETS)</a>	<a href="#">EXTENDER EXT-POE2 PULSAR</a>	<a href="#">ACCESS CONTROLLER ASC2102B-T DAHUA</a>	<a href="#">POWER DISTRIBUTION UNIT AK-SP-05A AKYGA</a>
					
	104.15 USD 104.15 USD	17.52 USD 17.52 USD	31.26 USD 31.26 USD	188.84 USD 188.84 USD	9.85 USD 9.85 USD
Number of served transitions	...	...	...	2 (two-way)	...
Standard	CVBS - PAL / NTSC	...	...	...	...
Rated voltage	...	230 V AC / 50 Hz	...	...	230 V AC / 50 Hz
Support	...	...	...	DAHUA ASC2204C-H	...
Total maximal current	...	10 A	...	...	10 A
Standards	...	...	PoE : IEEE 802.3at, IEEE 802.3af	...	...
Number of supported readers	...	...	...	4 pcs	...
Maximal total load	...	2300 W	...	...	2500 W
Input voltage	...	...	42 ... 57 V DC	...	...
Battery backup support	...	...	...	—	...
Input impedance	75 Ω	...	...	...	...
Response time	...	< 25 ns	...	...	< 25 ns
Output voltage	...	...	42 ... 57 V DC	...	...
Number of inputs	4 pcs BNC	...	1	...	...
Output impedance	75 Ω	...	...	...	...
Output lines	...	...	...	5 pcs - Relay	...
Number of outputs	4 pcs BNC	...	2	...	...
Galvanic (optical) isolation between signal inputs and outputs	1000 V peak	...	...	...	...
Number of outlets	...	5 grounded outlets 10A/250V 2 non-grounded outlets 2.5A/250V	...	...	5 grounded outlets 10A/250V
Alarm inputs / outputs	...	...	...	5 / 1	...
Opto-isolation between power and signal inputs / outputs	1000 V peak	...	...	...	...
Connector	...	...	3 x RJ-45 socket	...	...
Galvanic isolation between signal inputs	1000 V peak	...	...	...	...
Automatic delayed fuse	...	10 A / 250 V	...	...	10 A / 250 V
LED indicators	...	...	Link/Act	...	...
Galvanic isolation between signal outputs	1000 V peak	...	...	...	...
Leak current	...	< 0.5 mA	...	...	...
Gain adjustment	-5 ... +5 dB (adjust potentiometers are available after remove the cover)	...	...	...	...
DC filter to eliminate interferences	...	...	...	...	RFI ≤ 10 dB
Nominal voltage of surge suppressor	...	250 V / 50 Hz	...	...	250 V / 50 Hz
Communication	...	...	...	• RS-485, • Wiegand 34/26, • Control panel CAN (Controller Area Network)	...
Protection level of surge suppressor	...	≤ 1.3 kV (L/N)	...	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Bandwidth	9 MHz / 1 Vpp	...	...	...	...
Maximum energy absorption	...	...	...	...	150 J
Transmission error	0.75 % (f=3.58MHz, Vin=1Vpp)	...	...	...	...
Nominal stroke current	...	2 kA (L/N) - (8/20µs)	...	...	...
Assembly	To the wall	...	...	...	...
Switch	...	two-way, with light indication	...	...	with light indication
Power supply	12 V DC / 300 mA	...	...	12 V DC / 1 A	...
Color	...	...	...	...	Black
Supported data rates	...	...	<ul style="list-style-type: none"> <li>• Range : 100 m - Input, 100 m - 2 x Output,</li> <li>• Supported data rates : 10 / 100 Mbps - Fast Ethernet</li> </ul>	...	...
Maximum stroke current	...	6.5 kA (L/N) - (8/20µs)	...	...	4.5 kA
Length of the cable	...	1.45 m	...	...	1.8 m
Main features	...	...	...	<ul style="list-style-type: none"> <li>• 20 000 indexed users</li> <li>• History of 30 000 events</li> <li>• Function to prevent of multiple use of the same code/card to gain access (anti-passback)</li> <li>• Door Left Open and Door Forced Open alarms</li> <li>• Watchdog built-in</li> <li>• Possibility to mount on a wall, or on the DIN TS-35 rail</li> </ul>	...
Output power	...	...	max. 15.4 W / port PoE max. 20 W (total)	...	...
Operation temp	...	...	...	-30 °C ... 60 °C	5 °C ... 50 °C
Permissible relative humidity	...	...	...	max. 95 % (non-condensing)	...
Protections	...	...	<ul style="list-style-type: none"> <li>• Overvoltage</li> <li>• Overload</li> <li>• Short-circuit</li> </ul>	...	...
Housing	...	Plastic - non-flammable	Metal	...	Plastic (ABS)
Operation temp. / Relative humidity	...	...	-10 ... 40 °C / 10 ... 90 %	...	...
Weight	0.310 kg	0.44 kg	0.11 kg	0.384 kg	0.306 kg
Dimensions	213 x 36 x 93 mm	370 x 65 x 44 mm	81 x 77 x 26 mm	209 x 117 x 51 mm	305 x 50 x 40 mm
Manufacturer / Brand	DELTA	...	PULSAR	DAHUA	AKYGA
Guarantee	3 years	2 years	2 years	3 years	2 years