



	HANDS-FREE SWITCH AD-TL-6497/DIMM 5 V - 24 V DC ORNO	SWITCH POE CS4010-8GT-110 8-PORT DAHUA
		
	4.65 EUR 4.65 EUR	272.66 EUR 272.66 EUR
Application	Works with LED lighting	...
Rated voltage	5 V - 24 V DC	...
Maximal total load	<ul style="list-style-type: none"> • 5 V = 40 W • 12 V = 96 W • 24 V = 120 W 	...
LAN ports	...	<ul style="list-style-type: none"> • 8 x RJ45 10/100/1000 Base-T (1 x Hi-PoE (802.3bt) + 7 x PoE (802.3af/at)), • 2 x RJ45 10/100/1000 Base-T - Uplink
Total maximal current	8 A	...
Detection range	10 mm ... 60 mm	...
Detection method	Passive Infra Red (PIR)	...
Transmission speed	...	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps : 8 LAN & PoE ports, • 10 / 100 / 1000 : 2 Uplink ports
Number of inputs	0	...
Number of outputs	1	...
Connector type	PCB (soldering)	...
Wireless	—	...
Mobile phones support	—	...
Maximal output power	...	<ul style="list-style-type: none"> • 90 W / port Hi-PoE / PoE 802.3bt - Port 1 • 30 W / port PoE 802.3af/at - 2 ... 8 ports
Maximal total power	...	110 W
MAC addresses table	...	8k
Management	...	✓
Operation modes	...	Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6
"Index of Protection"	IP20	...
Color	—	...
LED diodes	...	Power, System, PoE, Link/Act

Main features	<ul style="list-style-type: none"> • High power - max. 120 W • Possibility to adjust the light intensity depending on your needs • Small dimensions • Possible assembly in a profile • Simple and quick device installation 	<ul style="list-style-type: none"> • Switch is managed through the web and the cloud (DoLynk Care application) • PoE power mode : The device supports 8-pin power supply - wires : 1-2(+), 3-6(-), 4-5(+), 7-8(-) • Intelligent management of Power Supply Unit power's output stage • protection against lightning discharges and voltage differences and strokes between devices • Watchdog PoE • Loop Protection • Compliance with the LLDP protocol • Spanning Tree STP/RSTP • Port Based VLAN : 32 • Data Flow Control (802.3x) • DHCP client • RESET button • Possibility to mount to the wall
Certificates	...	CE
Protections	...	<ul style="list-style-type: none"> • Protection against lightning discharges (common/differential) : 4 / 2 kV • Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV
Housing	—	Desktop, Metal
Power supply	...	54 V DC / 2.22 A (power adapter included)
Power consumption	...	max. 110 W
Operation temp	...	-10 °C ... 55 °C
Weight	0.001 kg	0.52 kg
Dimensions	48 x 10 x 6 mm	190 x 106 x 30 mm
Manufacturer / Brand	ORNO	DAHUA
Guarantee	2 years	3 years