






	EXPANSION PLUG KW-10/5X80 KLIMAS	RFID PROXIMITY CARD ATLO-104*P200	RFID PROXIMITY CARD ATLO-114*P100	REAR MOUNTING BASE USP-UDMK-T FOR SOLAR PANELS	HDD ENCLOSURE Y-3035 UNITEK	AHD, HD-CVI, HD-TVI, PAL CAMERA BCS-B- TA15FSR4(2,0) - 5 Mpx 2.8 mm BCS BASIC
						
	0.12 GBP 0.12 GBP	51.33 GBP 51.33 GBP	38.39 GBP 38.39 GBP	6.28 GBP 6.28 GBP	27.02 GBP 27.02 GBP	26.69 GBP 26.69 GBP
Material	Aluminum
Material	• Expansion plug, Polypropylene • Screw, Steel galvanized
Standard	AHD, HD-CVI, HD-TVI, PAL
In package	...	200 pcs The price for package	100 pcs The price for package
Supported hard drives	1 x SATA III, 2.5" / 3.5"	...
Drilling diameter	10 mm
Standard	...	Unique EM 125kHz	Unique EM 125kHz
Expansion plug length	50 mm
Compatibility	...	EM4100/4102	EM4100/4102
Possibility of programming the serial number (ID)	...	—	—
Outputs	1 x USB 3.1, max. 5 Gb/s	...
Operation state indication	LED diodes	...
Ability to write to internal memory	...	—	—
Screw dimensions	Ø 5 x 80 mm, PZ-2
Serial Number overprint	...	—	—
Application	• Concrete • Solid clay brick • Solid sand-lime brick
Main features	...	• Range : ~ 11 cm • The TK-4100 chip	• Range : ~ 15 cm • The TK-4100 chip
Resolution	2880 x 1620 - 5 Mpx - HD-CVI only : Aspect Ratio 16 : 9 , 2592 x 1944 - 5 Mpx - AHD / HD-TVI only , 2560 x 1440 - 4 Mpx , 1920 x 1080 - 1080p , 960 x 576 - 960H
Sensor	1/2.7" Progressive Scan CMOS
Lens	2.8 mm, F1.2
View angle	109 °
Range of IR illumination	40 m
IR illuminator power adjustment	Automatic
Video output	AHD / HD-CVI / HD-TVI / PAL, 1 Vpp / 75 Ω
OSD menu	✓
Main features	• D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Sharpness - sharper image outlines • AGC - Automatic Gain Control • White Balance - ATW/Manual • Day/night mode • ICR - Movable InfraRed filter • Mirror - Mirror image
Power supply	12 V DC / 2 A (power adapter included)	12 V DC / 290 mA
Power consumption	≤ 3.4 W
Housing	Desktop, Plastic	Compact, Metal
Color	White

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

"Index of Protection"	IP67
Operation temp	-30 °C ... 60 °C
Weight	...	0.006 kg	0.006 kg	0.16 kg	0.2 kg	0.241 kg
Dimensions	...	86 x 54 x 1 mm	85 x 54 x 2 mm	96 x 80 x 72 mm	183 x 117 x 35 mm	Ø 66 x 154 mm
Manufacturer / Brand	KLIMAS	ATLO	ATLO	...	UNITEK	BCS BASIC
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00