


	<a href="#">BATTERY-FREE WIRELESS DOORBELL OR-DB-MT-156 AC 230V ORNO</a>	<a href="#">SAFE OPTI-SAMSON</a>	<a href="#">IP SPEED DOME CAMERA OUTDOOR IPC6612SR-X25-VG LightHunter - 1080p 5... 125 mm UNIVIEW</a>
			
	21.20 EUR 21.20 EUR	30.59 EUR 30.59 EUR	1127.37 EUR 1127.37 EUR
Standard	...	...	TCP/IP
Signaling mode	Optical - sound signaling	...	...
Number of ring-tones	36	...	...
Sensor	...	...	1/2.8 " Progressive Scan CMOS
Battery power supply	...	Alkaline batteries - 4 x LR6 (AA), 1.5 V	...
Matrix size	...	...	2.1 Mpx
Volume adjustment	60 ... 90 dB - 4-step	...	...
Operation range	max. 200 m in open area	...	...
Frequency band	433.92 MHz	...	...
Resolution	...	...	1920 x 1080 - 1080p , 1280 x 960 1.3 Mpx , 1280 x 720 720p
Manufacturer code	...	* 1 5 9 * - opening and closing the lock	...
Plate thickness	...	1.5 mm	...
Lens	...	...	5 ... 125 mm
Main features	<ul style="list-style-type: none"> <li>• The doorbell button is powered by an electromagnetic transducer, does not require any battery</li> <li>• Learning function - The number of cooperated doorbell buttons (transmitters) can be increased as required</li> </ul>	...	...
View angle	...	...	54 ° ... 2.6 °
Country of origin	...	China	...
Optical zoom	...	...	x 25
Operation temp	-40 °C ... 65 °C	...	...
Digital zoom	...	...	—
Range of IR illumination	...	...	150 m
Video output	...	...	—
Preset rotation speed	...	...	<ul style="list-style-type: none"> <li>• 180 °/s (horizontal)</li> <li>• 80 °/s (vertical)</li> </ul>
Rotation speed (manual control)	...	...	<ul style="list-style-type: none"> <li>• 2 °/s ... 75 °/s (horizontal)</li> <li>• 2 °/s ... 75 °/s (vertical)</li> </ul>
Horizontal rotation range	...	...	360 ° - continuous

Vertical rotation range	...	...	-15 ° ... 90 °
RS-485 interface	...	...	✓
Number of presets	...	...	1024
Horizontal scan	...	...	✓
Route settings	...	...	16
Image compression method	...	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	...	2 / 1
Audio	...	...	<ul style="list-style-type: none"> <li>• External microphone input</li> <li>• Audio output</li> <li>• Bi-directional audio streaming support</li> <li>• Audio detection</li> </ul>
Main stream frame rate	...	...	25 fps @ 1080p
Network interface	...	...	10/100 Base-T (RJ-45)
WEB Server	...	...	Built-in
Max. number of on-line users	...	...	32
ONVIF	...	...	✓
Memory card slot	...	...	Micro SD memory cards up to 256GB support (possible local recording)
Mobile phones support	...	...	Port 37777 <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">EZView</a></li> <li>• iOS (iPhone): Free application <a href="#">EZView</a></li> </ul>
Default IP address	...	...	DHCP or 192.168.1.13
Default admin user / password	...	...	admin / 123456
Web browser access ports	...	...	80, 554
PC client access ports	...	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application <a href="#">EZStation</a>
Mobile client access ports	...	...	80
Port ONVIF	...	...	80
RTSP URL	...	...	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream

Main features	...	<ul style="list-style-type: none"> <li>• Keypad lock after three incorrect code entries</li> <li>• Emergency opening with the key</li> <li>• Optical and acoustic operations signaling</li> <li>• Incorrect code entering indication</li> <li>• Low battery level alarm</li> <li>• Electronic lock with 3-8 digital code</li> </ul>	<ul style="list-style-type: none"> <li>• Intelligent Object Tracking</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Day/night mode</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• Configurable Privacy Zones - 24</li> <li>• Motion Detection</li> <li>• Tamper signaling</li> <li>• Image rotation and mirror</li> <li>• Adaptive adjusting of the IR illuminator power to the lens zoom and outdoor light conditions</li> <li>• Overvoltage protection : 6 kV</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area</li> </ul>
Power supply	<ul style="list-style-type: none"> <li>• 230 V AC - Wireless doorbell,</li> <li>• Electromagnetic transducer - Doorbell button</li> </ul>	...	<ul style="list-style-type: none"> <li>• PoE (802.3at),</li> <li>• 12 V DC / 3 A (power adapter included)</li> </ul>
Power consumption	...	...	max. 25 W
Housing	...	...	Speed Dome, Metal + Plastic
Color	...	Black	White + Black
Operation temp	...	...	-40 °C ... 65 °C
"Index of Protection"	<ul style="list-style-type: none"> <li>• IP44 - Doorbell button</li> <li>• IP20 - Wireless doorbell</li> </ul>	...	IP66
Vandal-proof	...	...	—
Weight	<ul style="list-style-type: none"> <li>• 0.05 kg - Doorbell button</li> <li>• 0.07 kg - Wireless doorbell</li> </ul>	3.55 kg	3.5 kg

Dimensions	<ul style="list-style-type: none"> <li>• 50 x 82 x 22 mm - Doorbell button</li> <li>• 81 x 81 x 72 mm - Wireless doorbell</li> </ul>	310 x 200 x 200 mm	Ø 220 x 370 mm
Supported languages	...	...	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovenian, Hungarian, Italian
Manufacturer / Brand	ORNO	Opticum	UNIVIEW
Guarantee	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00