




	CAMERA BRACKET TR-JB03-G-IN-BLACK UNIVIEW	CONNECTOR WITH ELASTIC SEALING F/7.0-G	TV OR MONITOR MOUNT BRATECK-FS22-44TP
			
	16.25 EUR 16.25 EUR	0.35 EUR 0.35 EUR	45.33 EUR 45.33 EUR
Connector type	...	"F" Straight plug	...
Attachment of connector elements	...	Twisted-on	...
Neck diameter	Ø 109 mm
Shield fastening	...	Twisting-on	...
Suitable for cameras	UNIVIEW
Wire mounting	...	—	...
Application	...	Coaxial cable	...
Cable diameter	...	max. 7.0 mm	...
Distance from mounting surface	38 mm
Impedance	...	75 Ω	...
Material	Aluminum	Metal	...
Mounting standard	VESA : 100 x 100, 200 x 100, 200 x 200, 300 x 200, 300 x 300, 400 x 200, 400 x 300, 400 x 400
Screen size range	32 " ... 55 "
Example of application	...	<ul style="list-style-type: none"> • RG6 • HFEK • Triset113 	...
Bearing capacity	35 kg
Color	Black	...	Black
Tilt adjustment	-10 ° ... 10 °
Horizontal rotation	—
Rotation in the plane of the screen	—
Main features	...	<ul style="list-style-type: none"> • Wide frequency range • Corrosion resistance • Elastic sealing 	Adjustable shelf height in the range of 60 cm
Weight	0.19 kg	0.005 kg	12 kg
Dimensions	113 x 109 x 38 mm	Ø 11 mm x 20 mm	1170 ... 1470 x 600 x 400 mm
Manufacturer / Brand	UNIVIEW	...	BRATECK
Guarantee	3 years	2 years	2 years