




	INSULATION STRIPPER HT-325	EXTENDER RECEIVER HDMI+USB-EX-100/RX SIGNAL	PIR DETECTOR SLIM-PIR- PRO SATEL
			
	22.52 CAD 22.52 CAD	77.30 CAD 77.30 CAD	66.77 CAD 66.77 CAD
Device type	...	Receiver	...
Pyroelectric sensor	Double
Material	Metal / PET
Sensor type	Passive Infra Red (PIR)
Range	20 x 24 m, 90 °
Application	Cable diameter : Ø 4.5 mm ... 25 mm	...	Indoor
Sensitivity adjustment	Possibility to set 1 of 16 sensitivity levels
Pet immunity	—
Supported HDMI resolutions	...	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	...
Alarm time	2 s
Maximal transmission range	...	100 m UTP cat. 5e, 6	...
Protocols	...	HDbiT	...
Maximal outputs load	40 mA / 24 V DC
Digital temperature compensation	✓
Main features	...	<ul style="list-style-type: none"> • Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse • The devices do not require direct connection, they also operate via the LAN network • Audio transmission via network 	...
Target speed range	0.2 ... 3 m/s
Power supply	...	5 V DC / 1 A (power adapter included)	12 V DC / 23 mA (max)
Permissible relative humidity	...	20 % ... 90 % (non-condensing)	...

Main features	High durability tool, made from high quality materials	...	<ul style="list-style-type: none"> • Compliance to EN 50131-2-4 @ Grade 3 standard, • Tamper detection - opening the enclosure, removing from mounting surface, • Built-in parametric resistors 2EOL: 2 x 1.1kΩ, 2 x 4.7 kΩ, 2 x 5.6 kΩ, • Remote on/off of the LED indicator and choice of lighting color from 7 colors, • Active IR Anti-Masking, • Remote controlled (not included), • Creep zone control
Operation temp	...	-10 °C ... 60 °C	-10 °C ... 55 °C
Weight	0.12 kg	0.168 kg	0.11 kg
Dimensions	165 x 44 x 35 mm	110 x 89 x 26 mm	62 x 137 x 42 mm
Manufacturer / Brand	...	SIGNAL	SATEL
Guarantee	2 years	2 years	5 years