



	ACCESS CONTROLLER MODULE MC16-PAC-EX-1 ROGER	LED FLOODLIGHT WITH MOTION SENSOR AD- NL-6254BLR4 ADVITI
		
	336.18 EUR 336.18 EUR	16.19 EUR 16.19 EUR
Number of served transitions	1	...
Luminous flux	...	2400 lm
Inputs	8	...
Outputs	8	...
Light color	...	Neutral, 4000 K
Number of users	max. 12000 - Number of identifiers	...
Twilight switch	...	✓
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.	...
Nominal power	...	30 W
Number of permissions per ID	100	...
Buffer memory	8 000 000 events buffer	...
Power factor	...	0.8
MCT readers support	16 pcs	...
Readers connections	4 pcs - Wiegand / PRT	...
CRI	...	> 80
Number of login points	2	...
Number of access terminals	4	...
Number of access zones	2	...
Number of alarm zones	2	...
Number of automation nodes	2	...
Battery backup support	12 V / 7 Ah	...
Communication	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RS-485 interface • RACS 5 v2 (Roger) 	...
Housing	...	Aluminum

Main features	<ul style="list-style-type: none"> • Integrated support in VISO EX software • Functions in the VISO EX system: - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system - unlimited - division of the system into partitions operated by independent operators - tool for integration with RACS5 (API) systems - integration with many systems (elevator systems, building applications, SMS, BMS, PSIM, VMS, Active Directory systems) 	<ul style="list-style-type: none"> • LED SMD diodes • LED lifetime 30 000 h • Solid workmanship • PIR detector - Built-in, Range : 4 ... 8 m, Detection angle : 120 ° • PIR detection sensitivity adjustment, • Sensitivity adjustment of the twilight sensor : 10 ... 2000 lx, • Lighting time adjustment : 10 ... 600 s, • IK rating : IK04
"Index of Protection"	...	IP44
Power supply	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC 	230 V AC
Operation temp	5 °C ... 40 °C	-20 °C ... 50 °C
Permissible relative humidity	10 % ... 95 % (non-condensing)	...
Weight	0.14 kg	0.38 kg
Dimensions	175 x 72 x 30 mm	155 x 170 x 65 mm
Manufacturer / Brand	ROGER	ORNO / ADVITI
Guarantee	3 years	3 years