





	<a href="#">ACCESS CONTROLLER PR621 ROGER</a>	<a href="#">ACCESS CONTROLLER ASC3202B DAHUA</a>	<a href="#">POWER CORD CABLE CEE-77/1.5M 1.5 m</a>	<a href="#">ACCESS CONTROLLER DS-K2602T Hikvision</a>
				
	107.95 EUR 107.95 EUR	504.82 EUR 504.82 EUR	3.49 EUR 3.49 EUR	596.75 EUR 596.75 EUR
Number of served transitions	...	2	...	...
Support	...	Cooperation with the access control systems	...	...
Relay contacts load	1.5 A / 30 V	...	...	...
Cable	...	...	3 x 0.75 mm <sup>2</sup> / Angular plug (Schuko)	...
Keyboard built-in	—	...	...	...
Number of supported readers	...	<ul style="list-style-type: none"> <li>• 2 pcs RS-485,</li> <li>• 2 pcs Wiegand</li> </ul>	...	<ul style="list-style-type: none"> <li>• 4 pcs @ RS-485,</li> <li>• 4 pcs @ Wiegand</li> </ul>
Length of the cable	...	...	1.5 m	...
Voltage	...	...	max. 250 V	...
Battery backup support	—	—	...	max. 7 Ah
Alarm inputs / outputs	...	2 / 2	...	...
Current	...	...	max. 10 A	...
Input lines	3	...	...	<ul style="list-style-type: none"> <li>• 4 pcs - Alarm inputs,</li> <li>• 2 pcs - Reed switch ,</li> <li>• 2 pcs - Door/gate opening button,</li> <li>• 5 pcs - Tamper</li> </ul>
Environment class	IV	...	...	...
Output lines	3	...	...	<ul style="list-style-type: none"> <li>• 2 pcs - Lock relay,</li> <li>• 4 pcs - Relay</li> </ul>
Network protocols	...	P2P, IPv4, DNS, DDNS, TCP, UDP, ONVIF CGI	...	...
Operation modes	...	<ul style="list-style-type: none"> <li>• Main control mode</li> <li>• Sub control mode</li> </ul>	...	...
Communication	<ul style="list-style-type: none"> <li>• RS-485</li> <li>• RACS (Roger)</li> </ul>	<ul style="list-style-type: none"> <li>• 3 x RS-485,</li> <li>• 2 x Wiegand 34/26,</li> <li>• 1 x Ethernet 10 / 100 Mbps (RJ-45)</li> </ul>	...	<ul style="list-style-type: none"> <li>• RS-485,</li> <li>• Ethernet,</li> <li>• Wiegand (w26 / w34),</li> <li>• Open Supervised Device Protocol (OSDP)</li> </ul>
SAP Code	...	...	...	302913795

Main features	<ul style="list-style-type: none"> <li>• Unique EM 125kHz proximity reader built-in</li> <li>• PRT series readers support</li> <li>• 1000 indexed users</li> <li>• History of 250 000 events</li> <li>• 99 General Purpose Schedules</li> <li>• 250 access groups</li> <li>• Tamper detection - removing from mounting surface</li> <li>• Function to prevent of multiple use of the same code/card to gain access (anti-passback)</li> </ul>	<ul style="list-style-type: none"> <li>• Support for 2 doors (2x door sensor, 2x exit button, 2x alarm line, 2x lock control)</li> <li>• 1000 indexed users</li> <li>• Support up to 3000 finger prints</li> <li>• Memory of 5000 RFID cards</li> <li>• Support storage of 300 000 records</li> <li>• 128 General Purpose Schedules</li> <li>• Identification modes : RFID card, remote access, PIN, Fingerprint - Any combination of the above</li> <li>• Tamper protections</li> <li>• Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress</li> <li>• Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value</li> <li>• Beep signal - Buzzer</li> <li>• White list, Black list</li> <li>• Web-Server built-in</li> <li>• Software update via network</li> <li>• Monitoring and configuration through network - SmartPSS Lite application</li> <li>• Power output 12 V DC / 1 A - supplying power to the lock</li> <li>• Support hardware I/O port configuration and export configuration diagrams</li> <li>• ONVIF compliance</li> </ul>	<ul style="list-style-type: none"> <li>• Very easy and quick assembly</li> <li>• Solid workmanship</li> </ul>	<ul style="list-style-type: none"> <li>• 100000 indexed users</li> <li>• History of 300000 events</li> <li>• Remote programming from PC</li> <li>• Metal housing</li> </ul>
Power supply	10 ... 15 V DC	<ul style="list-style-type: none"> <li>• 12 V DC / 2.5 A</li> <li>• PoE (802.3at)</li> </ul>	...	100 ... 240 V AC
Power consumption	...	<ul style="list-style-type: none"> <li>• ≤ 2 W (standby)</li> <li>• max. 20.4 W @ 12 V (operation)</li> <li>• max. 14.4 W @ PoE (operation)</li> </ul>	...	...
Housing	...	Plastic (PC + ABS)	...	...
Color	...	White	...	...
IK rating	...	IK06	...	...
Operation temp	-25 °C ... 60 °C	-10 °C ... 55 °C	...	-20 °C ... 65 °C
Permissible relative humidity	10 ... 95 % (non-condensing)	5 % ... 95 % (non-condensing)	...	10 % ... 90 % (non-condensing)
Weight	0.15 kg	0.72 kg	0.15 kg	4.6 kg

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Dimensions	85 x 85 x 27 mm	186 x 186 x 58 mm	...	373 x 345 x 98 mm
Manufacturer / Brand	ROGER	DAHUA	...	Hikvision
Guarantee	3 years	3 years	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00