




	CLEANING PASTE PEVALIN-PROFESSIONAL/250 TUBE 250 ml TESA	ACCESS POINT UNIFI-U6-LR UBIQUITI	RFID PROXIMITY CARD ATLO-104N*P200
			
	60.60 DKK 60.60 DKK	1927.02 DKK 1927.02 DKK	448.19 DKK 448.19 DKK
Package	Tube 250 ml
Frequency range	...	<ul style="list-style-type: none"> • 5 GHz, • 2.4 GHz 	...
In package	200 pcs The price for package
Standard	Unique EM 125kHz
Compatibility	EM4100/4102
Possibility of programming the serial number (ID)	—
Ability to write to internal memory	—
Serial Number overprint	✓
Antenna type	...	<ul style="list-style-type: none"> • 4Tx 4Rx MIMO @ 2.4 GHz - 4 dBi, • 4Tx 4Rx MU-MIMO&OFDMA @ 5.0 GHz - 5.5 dBi Integrated - 4 x Omnidirectional antenna	...
Standards	...	<ul style="list-style-type: none"> • IEEE 802.11a, • IEEE 802.11b, • IEEE 802.11g, • IEEE 802.11n, • IEEE 802.11ac, • IEEE 802.11ax, • IEEE 802.1Q VLAN 	...
Baud rates	...	<ul style="list-style-type: none"> • 2400 Mbps @ 5 GHz, • 600 Mbps @ 2.4 GHz 	...
Protections	...	WPA-PSK, WPA-Enterprise (WPA/WPA2/WPA3)	...
LAN ports	...	1 x 10/100/1000 Mbps	...
Operating system	...	UniFi WiFi Enterprise System	...
Transmitter power	...	<ul style="list-style-type: none"> • 26 dBm @ 2.4 GHz (max) • 26 dBm @ 5.0 GHz (max) 	...
Power supply PoE	...	Ubiquiti Passive PoE	...
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3at), • 48 V / 0.5 A - PoE Adapter (not included) 	...
Power consumption	...	16.5 W	...

Main features	...	<ul style="list-style-type: none"> • Possibility to mount on the wall or ceiling • UniFi WiFi Enterprise System • AP placement and RF maps • Easy and uniform management system for many devices • Intuitive installation and configuration of many advanced functions • Support for WiFi4/WiFi5/WiFi6 • MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network • OFDMA • QoS • Bluetooth interface • "Index of Protection" : IP54 	<ul style="list-style-type: none"> • Serial Number Format : 8H10D + WEG24A • Range : ~ 11 cm • The TK-4100 chip
Operation temp	...	-30 °C ... 60 °C	...
Permissible relative humidity	...	5 % ... 95 %	...
Weight	...	<ul style="list-style-type: none"> • 0.82 kg • 1.05 kg (with mounting kits) 	0.006 kg
Dimensions	...	Ø 220 x 48 mm	86 x 54 x 1 mm
Manufacturer / Brand	TESA	UBIQUITI	ATLO
Guarantee	2 years	2 years	2 years