



	ACCESS CONTROLLER ASC2202B-S DAHUA	CONVERTER VGA+AU/HDMI-ECO
		
	215.46 EUR 215.46 EUR	9.33 EUR 9.33 EUR
Number of served transitions	2 (one-way)	...
Support	DAHUA	...
Inputs	...	<ul style="list-style-type: none"> • VGA, • Audio (Jack stereo socket)
Number of supported readers	4 pcs	...
Outputs	...	HDMI
Battery backup support	—	...
Output lines	2 pcs - Relay	...
Communication	<ul style="list-style-type: none"> • RS-485, • Ethernet, • Wiegand 	...
Main features	<ul style="list-style-type: none"> • 100000 indexed users • History of 500000 events • Remote programming from PC • Function of protection against multiple use of the same card for access (anti-passback) • Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value • Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress • Possibility to mount on a wall, or on the DIN TS-35 rail 	...
Default IP address	192.168.0.2	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Operation temp	-30 °C ... 60 °C	...

Permissible relative humidity	5 % ... 90 % (non-condensing)	...
Manufacturer / Brand	DAHUA	...
Supported VGA input resolutions	...	1024 x 768 @ 60 / 70 / 75 / 85 Hz 1152 x 864 @ 75 Hz 1280 x 720 @ 60 Hz 1280 x 768 @ 60 Hz 1280 x 800 @ 60 Hz 1280 x 960 @ 60 Hz 1280 x 1024 @ 60 Hz 1360 x 768 @ 60 Hz 1440 x 900 @ 60 Hz 1600 x 1200 @ 60 Hz 1680 x 1050 @ 60 Hz 1920 x 1080 @ 60 Hz
Supported HDMI output resolutions	...	1024 x 768 @ 60 / 70 / 75 / 85 Hz 1152 x 864 @ 75 Hz 1280 x 720 @ 60 Hz 1280 x 768 @ 60 Hz 1280 x 800 @ 60 Hz 1280 x 960 @ 60 Hz 1280 x 1024 @ 60 Hz 1360 x 768 @ 60 Hz 1440 x 900 @ 60 Hz 1440 x 1050 @ 60 Hz 1680 x 1050 @ 60 Hz 1600 x 1200 @ 60 Hz 1920 x 1080 @ 60 Hz
HDCP	...	—
Maximal range of HDMI transmission	...	15 m
Power supply	<ul style="list-style-type: none"> • PoE (802.3at), • 12 V DC / 4 A 	5 V DC - mini USB socket (power adapter not included)
Weight	0.27 kg	0.085 kg
Dimensions	155 x 116 x 50 mm	64 x 55 x 20 mm
Guarantee	3 years	2 years