



	IP CAMERA DS-2CD2347G2H-LI(2.8MM)(EF) ColorVu - 4 Mpx Hikvision	TV OR MONITOR MOUNT BRATECK-LPA39-223
		
	4103.34 NOK 4103.34 NOK	176.74 NOK 176.74 NOK
Standard	TCP/IP	...
Sensor	1/1.8 " Progressive Scan CMOS	...
Matrix size	4 Mpx	...
Mounting standard	...	VESA 75, 100, 200x100, 200
Screen size range	...	23 " ... 42 "
Bearing capacity	...	35 kg
Distance from mounting surface	...	45 ... 508 mm
Resolution	2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	...
Lens	2.8 mm	...
Tilt adjustment	...	-15 ° ... 10 °
View angle	111 °	...
Horizontal rotation	...	-90 ° ... 90 °
Rotation in the plane of the screen	...	± 3 °
White light LED illuminator range	40 m	...
Range of IR illumination	40 m	...
Memory card slot	Micro SD memory cards up to 512GB support (possible local recording)	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	—	...
Audio	—	...
Main stream frame rate	25 fps @ 4 Mpx	...
Network interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	6	...
ONVIF	✓	...

Main features	<ul style="list-style-type: none"> • Smart Hybrid Light / ColorVu technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • Possibility to turn off the LED illuminator • WDR - 130 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Smart motion detection (with recognizing people and vehicles) • Configurable Privacy Zones • Sharpness - sharper image outlines • Filtering of false alarms based on the recognition of persons and vehicles • video tampering • Intelligent image analysis : crossing the line (tripwire), intrusion, scene changing, detection of entry into the area / exit from the area - classification of people and vehicles, face detection 	...
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect 	...
Default IP address	192.168.1.64	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80	...
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Mobile client access ports	8000	...
Port ONVIF	80	...
RTSP URL	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 420 mA 	...
Power consumption	<ul style="list-style-type: none"> • ≤ 6 W @ PoE • ≤ 5 W @ 12 V DC 	...
Housing	Dome, Metal	...
Color	White	Black
"Index of Protection"	IP67	...
Vandal-proof	—	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.77 kg	2.7 kg

Dimensions	Ø 138 x 115 mm	226 x 229 x (45 ... 508) mm
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian	...
Manufacturer / Brand	Hikvision	...
SAP Code	311323593	...
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00