




	IP CAMERA APTI-14C4-2812G - 1.3 Mpx 2.8 ... 12 mm	A WEAKENING CUTTER IN JUNCTION BOXES F- CUTTER-V2 SIMET	POWER DISTRIBUTION UNIT ACAR-SMART (6 OUTLETS)
			
	66.52 EUR 66.52 EUR	1.21 EUR 1.21 EUR	21.84 EUR 21.84 EUR
Material	...	Plastic	...
Standard	TCP/IP
Application	...	SIMET junction boxes	...
Rated voltage	230 V AC / 50 Hz
Digital Image Processor	Hisilicon 3518C
Protection level	≤ 1.3 kV
Sensor	1/3 " Sony CMOS IMX225
Matrix size	1.4 Mpx
Nominal load current	10 A (total)
Holes diameter	...	7 mm, 11 mm, 15 mm	...
Main features	...	The cutter also makes it easier to open the box cover	...
Maximum stroke current	6.5 kA (L/N)
Resolution	1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Nominal stroke current	2 kA (L/N) 8/20 μs 8/20 μs
Leak current	< 0.5 mA
Response time	< 25 ns
Number of output outlets	6
Switch	2 pcs
Length of the cable	1.4 m
Lens	2.8 ... 12 mm, 2 Mpx
View angle	81 ° ... 23 ° (manufacturer data) 81 ° ... 34 ° (our tests result)
S/N ratio	> 50 dB
Range of IR illumination	40 m
IR illuminator power adjustment	Automatic
Image compression method	H.264
Bitrate	64 ... 12000 kbps
Main stream frame rate	25 fps - 1024p
Network interface	10/100 Base-T (RJ-45)
Alarm inputs / outputs	—
Network protocols	TCP/IP, HTTP, DHCP, FTP, DNS, DDNS, RTSP, NTP
Audio	—

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

WEB Server	Built-in
Max. number of on-line users	10
ONVIF	2.4
RS-485 interface	—
Mobile phones support	—
Default admin user / password	admin / admin
Default IP address	192.168.1.168
Web browser access ports	80
PC client access ports	80
Mobile client access ports	80
Port ONVIF	80
RTSP URL	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream
Main features	<ul style="list-style-type: none"> • ICR - Movable InfraRed filter • Possibility to change the resolution, quality and bit rate • Motion Detection • Privacy zones • Configurable: brightness, contrast, saturation • Sharpness - sharper image outlines • Mirror - Mirror image • Day/Night mode - configurable
Power supply	12 V DC / 710 mA
Housing	Compact, Metal	...	Plastic - non-flammable
Color	Dark graphite
"Index of Protection"	IP66
Operation temp	-20 °C ... 55 °C
Weight	0.68 kg	0.005 kg	0.4 kg
Dimensions	287 x 96 x 88 mm	63 x 33 x 17 mm	138 x 100 x 63 mm
Supported languages	English, Bulgarian, French, Spanish, Dutch, German, Polish, Russian, Turkish, Italian
Manufacturer / Brand	APTI	SIMET	...
Guarantee	2 years	2 years	2 years