



	POLE MOUNT USH-M1	IP CAMERA IPC2122LB-ADF40KM-H - 1080p 4 mm UNIVIEW
		
	4746.67 HUF 4746.67 HUF	48748.57 HUF 48748.57 HUF
Standard	...	TCP/IP
Support	SH-230/210/145	...
Material	Magnelis - carbon steel, coated with a zinc-aluminum-magnesium alloy	...
Sensor	...	1/2.7 " Progressive Scan CMOS
Number of fastening elements	2	...
Matrix size	...	2.1 Mpx
Mast diameter	Ø 50 mm (max)	...
Plate thickness	2 mm	...
Mounting holes distance	145 mm	...
Main features	Mounting to the mast with u-bolts	...
Resolution	...	1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	...	4 mm
View angle	...	91 °
Range of IR illumination	...	30 m
S/N ratio	...	> 52 dB
RS-485 interface	...	—
Memory card slot	...	Micro SD memory cards up to 128GB support (possible local recording)
Image compression method	...	Ultra 265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	<ul style="list-style-type: none"> • Microphone built-in, • Audio transmission via network, • Audio detection
Main stream frame rate	...	25 fps @ 1080p
Network interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in
Max. number of on-line users	...	32
ONVIF	...	✓
Mobile phones support	...	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView
Default IP address	...	DHCP or 192.168.1.13

Default admin user / password	...	admin / 123456
Web browser access ports	...	80, 554
PC client access ports	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	...	80
Port ONVIF	...	80
RTSP URL	...	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream
Main features	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Sharpness - sharper image outlines
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 580 mA
Power consumption	...	≤ 7 W
Housing	...	Compact, Metal + Plastic
Color	...	White
"Index of Protection"	...	IP67
Vandal-proof	...	—
Operation temp	...	-30 °C ... 60 °C
Weight	0.69 kg	0.38 kg
Dimensions	...	166 x 63 x 62 mm
Supported languages	...	Polish, English, Czech, Spanish, French, German, Portuguese, Slovak, Hungarian, Italian
Manufacturer / Brand	...	UNIVIEW
Guarantee	2 years	3 years