




	<a href="#">ACCESS POINT 4G LTE +ROUTER RUT956 Dual SIM 2.4 GHz 300 Mbps Teltonika</a>	<a href="#">SWITCHING ADAPTER PS65-15-DIN ACO</a>	<a href="#">MODEM 4G LTE, MOBILE ROUTER TL-M7350 Wi-Fi 300Mb/s TP-LINK</a>
			
	2692.74 SEK 2692.74 SEK	678.79 SEK 678.79 SEK	1096.63 SEK 1096.63 SEK
Frequency range	2.4 GHz	...	2.4 GHz
Application	...	ACO Video Doorphones	...
Adapter type	...	Switching	...
Power voltage	...	100 ... 240 V AC	...
Output voltage	...	15 V DC	...
Output voltage adjustment	...	—	...
Maximal load	...	4 A	...
Antenna type	2 x Omnidirectional antenna Wi-Fi - 3 dBi (SMA connector) , 2 x Omnidirectional antenna 4G LTE - 4 dBi (SMA-RP connector) 1 x Omnidirectional antenna GPS (SMA connector)	...	1 x WiFi - Internal antenna , 1 x 4G LTE - Internal antenna
Output power	...	65 W	...
Number of outputs	...	2 pcs	...
Efficiency	...	≤ 91 %	...
Housing type	...	DIN	...
Standards	IEEE 802.11 b/g/n, 4G, 3G, 2G, GNSS	...	IEEE 802.11 b/g/n, 4G LTE, 3G DC-HSPA+/HSPA/UMTS, 2G EDGE/GPRS/GSM
Baud rates	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 150 / 42 / 0.236 Mbps (4G / 3G / 2G)	...	• LTE : 150 / 50 Mbps, • 11n : 300 Mbps, • 11g : 54 Mbps, • 11b : 11 Mbps
LAN ports	• 1 x 10/100 Mbps - WAN • 3 x 10/100 Mbps - LAN	...	—
LED indicators	Power, WAN, 3 x LAN, LTE, Signal indicator	...	...

Network type	4G, 3G, 2G	...	<ul style="list-style-type: none"> <li>• 4G : FDD-LTE B1/B3/B7/B8/B20 - 2100 / 1800 / 2600 / 900 / 800 MHz</li> <li>• 3G : DC-HSPA+/HSPA/UMTS B1/B8 - 2100 / 900 MHz</li> <li>• 2G : Quad Band - 850 / 900 / 1800 / 1900 MHz</li> </ul>
Ports	...	...	<ul style="list-style-type: none"> <li>• 1 x micro USB - Battery charging</li> <li>• 1 x SIM socket</li> <li>• 1 x microSD</li> </ul>
Receiver sensitivity	...	...	<ul style="list-style-type: none"> <li>• 11b 11 Mbps : -87.5 dBm</li> <li>• 11g 54 Mbps : -74 dBm</li> <li>• 11n HT20 MCS7 : -70 dBm</li> <li>• 11n HT40 MCS7 : -68 dBm</li> </ul>
LTE	✓	...	...
QSS	—	...	...
Transmitter power	<ul style="list-style-type: none"> <li>≤ 20 dBm @ 2.4 GHz</li> <li>≤ 23 dBm @ 4G LTE</li> <li>≤ 24 dBm @ 3G WCDMA</li> <li>≤ 33 dBm @ 2G GSM</li> </ul>	...	< 20 dBm
WDS	—	...	...
DHCP server	✓	...	...
Protections	<ul style="list-style-type: none"> <li>• WPA2-Enterprise - PEAP</li> <li>• WPA2-PSK</li> <li>• WEP</li> <li>• WPA-EAP</li> <li>• WPA-PSK</li> <li>• AES-CCMP</li> <li>• TKIP</li> <li>• Auto Cipher modes</li> <li>• Client separation</li> <li>• SSID hiding</li> <li>• MAC addresses filtering</li> </ul>	<ul style="list-style-type: none"> <li>• Short-circuit</li> <li>• Overload</li> <li>• Overheat</li> </ul>	...
Management interface	Web browser, Teltonika RMS application, SMS, Port RS-232, Port RS-485	...	...

Main features	<ul style="list-style-type: none"> <li>• Support for IoT (Internet of Things) systems,</li> <li>• Ability to work as a Hotspot,</li> <li>• Support for VoIP technology,</li> <li>• 2 x SIM socket,</li> <li>• DHCP Relay support</li> <li>• DHCP client list</li> <li>• Static / dynamic routing</li> <li>• VPN support</li> <li>• Default address : 192.168.1.1</li> <li>• Configuration using the Teltonika RMS application</li> <li>• WAN Connection Backup - thanks to the fully functional WAN / LAN port, you can use various types of backup connections, including cable, fiber and DSL modems</li> <li>• Built-in GPS/GLONASS module,</li> <li>• Port RS-232,</li> <li>• Port RS-485,</li> <li>• Port USB 2.0,</li> <li>• Expanded I/O interface</li> </ul>	...	<ul style="list-style-type: none"> <li>• ON/OFF button</li> <li>• MENU button</li> <li>• RESET button</li> <li>• The microSD - max. 32 GB cards support</li> <li>• Color LCD : WiFi, INTERNET, Battery charge indicator, Wireless transmission statistics, Number of users, Network type, Signal indicator</li> <li>• Transmission encryption : WPA-PSK/WPA2-PSK</li> <li>• Black list</li> <li>• MAC addresses filtering</li> <li>• SSID hiding</li> <li>• DHCP server</li> <li>• DHCP client list</li> <li>• RNDIS support</li> <li>• Max. number of supported devices : 10</li> <li>• Backup time max. 8 h</li> <li>• Remote management - tpMiFi application</li> <li>• System requirements : Windows XP/Vista/7/8/10, Mac OS, Android, iOS (iPhone, iPad), Windows Phone</li> </ul>
Power supply	<ul style="list-style-type: none"> <li>• 9 V DC / 1 A (power adapter included)</li> <li>• 9 ... 30 V DC</li> <li>• 9 ... 30 V DC - Passive PoE, Powering from LAN1</li> </ul>	...	<ul style="list-style-type: none"> <li>• 2000 mAh Battery</li> <li>• 5 V DC / 1 A Charging via USB port</li> </ul>
Power consumption	≤ 7 W	...	...
Operation temp	-40 °C ... 75 °C	...	0 °C ... 35 °C
Permissible relative humidity	10 % ... 90 % (non-condensing)	...	10 % ... 90 % (non-condensing)
Weight	0.29 kg	0.22 kg	0.12 kg
Dimensions	110 x 100 x 50 mm	70 x 91 x 59 mm	106 x 66 x 16 mm
Manufacturer / Brand	Teltonika	ACO	TP-LINK
Guarantee	2 years	3 years	3 years