

	TV OR MONITOR MOUNT BRATECK-LPA49-686	MONITOR DESK MOUNT BRATECK-LDT66-C01	SMART LED LIGHTING CONTROLLER PIXELBOX/BLERBOX W1-E, 5 ... 12 V DC	WIRELESS REMOTE CONTROL EXTENSION VT2-SIG	OVERVOLTAGE LIMITER LE-412223 THREE-PHASE 2 TYPE LEGRAND	LITHIUM BATTERY BAT. CR2032*P6 ENERGIZER	LITHIUM BATTERY BAT. CR1632 ENERGIZER	ACCESS CONTROLLER WITH TEMPERATURE MEASUREMENT OPTI- ALZ1FR1D 4.5 mm - 1080p	ACCESS CONTROLLER DS- K2602T Hikvision
									
	117.51 CAD 117.51 CAD	13.45 CAD 13.45 CAD	37.85 CAD 37.85 CAD	43.31 CAD 43.31 CAD	124.27 CAD 124.27 CAD	6.00 CAD 6.00 CAD	2.24 CAD 2.24 CAD	79.40 CAD 79.40 CAD	887.80 CAD 887.80 CAD
Working frequency band	433.92 MHz
Operation range	30 m
Device type	Overvoltage limiter, Three-phase
Application	Works with LED lighting - digital (ARGB/RGB) 12V WS2811/WS2815 LED strips
In package	6 pcs The price for package
Scanning system	Progressive
Number of supported readers	• 4 pcs @ RS-485, • 4 pcs @ Wiegand
Rated voltage	5 ... 12 V DC	...	230 / 400 V AC, 50 / 60 Hz	3 V	3 V
Battery backup support	max. 7 Ah
Type (size)	CR2032	CR1632
Maximal voltage	320 V AC, 50 / 60 Hz
Optical zoom
Maximal total load	60 W (power), 20 mA (controlling)
Total maximal current	5 A
Mounting standard	VESA 200, 300 x 200, 300, 400 x 200, 400 x 300, 400, 600 x 400, 800 x 400, 800 x 600	VESA 100 x 100, 75 x 75
Class	2 type (Class C)
Number of inputs	1
Sensor	1/2.8 " SONY Starvis™ Back-illuminated CMOS 1/5 " GC2145	...
Screen size range	50 " ... 90 "	17 " ... 32 "
Protection level Up L/PE, N/PE	1.2 kV @ 8/20 µs (T2)
Matrix size	2.1 Mpx 2 Mpx	...
Pixel pitch	1.75 µm	...
Bearing capacity	75 kg	9 kg
Number of outputs	1 (power), 1 (controlling)
Nominal discharge current (L/PE, N/PE)	5 kA @ 8/20 µs (T2)
Connector type	screw terminals
Lens	4.5 mm 2.4 mm	...
Distance from mounting surface	69 ... 635 mm
View angle	68 ° 70 °	...
Maximum stroke current (L/N, L/PE, N/PE)	20 kA @ 8/20 µs (T2)
Resolution	1920 x 1080 - 1080p 800 x 600 - 0.48 Mpx	...
Input lines	• 4 pcs - Alarm inputs, • 2 pcs - Reed switch , • 2 pcs - Door/gate opening button, • 5 pcs - Tamper
Operation state indication	✓
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g
Tilt adjustment	-15 ° ... 5 °	-45 ° ... 45 °
Connectors type Standard	screw terminals
Mobile phones support	• The yBox free application on Android • The yBox free application on iOS
Range of IR illumination
Horizontal rotation	-60 ° ... 60 °	-90 ° ... 90 °	5 m	...
White light LED illuminator range	5 m	...
Rotation in the plane of the screen	± 3 °	360 °
Temperature measurement	✓	...
Output lines	• 2 pcs - Lock relay, • 4 pcs - Relay
Width in 17.5 mm modules	4
Temperature measurement range	35 °C ... 42 °C	...
Accuracy of temperature measurement	± 0.3 °C	...
Face recognition distance	0.5 m ... 2.3 m (max 30 000 faces in the database)	...
Communication	• RS-485, • Ethernet, • Wiegand (w26 / w34), • Open Supervised Device Protocol (OSDPI)
Temperature measurement distance	0.5 m ... 1.3 m optimal distance : 0.75 m	...
Internal memory	Support storage of 25 000 records	...
Video output

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

RS-485 interface	✓	...
Wiegand interface	✓	...
Memory card slot	---	...
Main features	...	Mount tube length 39.5 cm	<ul style="list-style-type: none"> Local control by physical button, schedule, timer, remote access, voice control, Controlling the color, effect, changing time allows any interior arrangement predefined effects, effects modification, Possibilities of controlling a digital LED strip consisting of 360 diodes, groups or matrices Possibility to cut off the power supply of the LED strip when it is switched off (energy saving) WiFi technology support 	<ul style="list-style-type: none"> 100000 indexed users History of 300000 events Remote programming from PC Metal housing
Permissible relative humidity	10% ... 90% (non-condensing)
Alarm inputs / outputs	0 / 2 (bolt control, signaling of exceeding the temperature)	...
Operation temp	-20 °C ... 50 °C	-20 °C ... 65 °C
Relay output	NO, NC	...
Audio	Speaker built-in	...
Network interface	10/100 Base-T (RJ-45)	...
SAP Code	302913795
Network protocols	IPv4, HTTP, HTTPS, TCP/IP	...
WEB Server	Built-in	...
Max. number of on-line users	20	...
ONVIF	---	...
RS-485	✓	...
Default IP address	DHCP / 192.168.1.88	...
Default admin user / password	admin / 12345	...
Web browser access ports	7080	...
PC client access ports	7080	...
Main features	<ul style="list-style-type: none"> Built-in LCD display showing the image from the video camera and the result of temperature measurement - 1024 x 600 px Day/Night mode (color/b&w/auto) RESET button Wiegand 26 Relay output operating modes: access control or notification of an exception 	...
Power supply	230 V AC from mains / 12 V DC from power adapter	12 V DC	100 ... 240 V AC
Power consumption	≤ 12 W	...
Housing	Plastic	Plastic, DIN, TS-35 rail mounting	Compact - Metal	...
Color	Black	Black	Black	Silver	...
"Index of Protection"	IP20	IP66	...
Operation temp	15 °C ... 25 °C - temperature measurement only in closed rooms (stabilized temperature)	...
Weight	10.6 kg	2.1 kg	0.02 kg	0.300 kg	0.334 kg	0.002 kg	0.001 kg	0.76 kg	...	4.6 kg
Dimensions	885 x 630 x (69 ... 635) mm	507 x 308 x 117 mm	36 x 26 x 19 mm	140 x 120 x 80 mm	71 x 83 x 70 mm	Ø 20 x 3.2 mm	Ø 15.9 x 3.1 mm	112 x 220 x 41 mm (with bracket)	...	373 x 345 x 98 mm
Length of the cable	64 cm	...
Supported languages	Polish, English, French, Spanish, German, Portuguese, Russian, Turkish, Italian	...
Manufacturer / Brand	...	BRATECK	BleBox	...	LEGRAND	ENERGIZER	ENERGIZER	APT	...	Hikvision
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	3 years	3 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00