





	<a href="#">TERMINAL COVER TBC-09</a>	<a href="#">IP CAMERA DS-2CD2087G2H-LIU(4MM)(EF) ColorVu - 8.3 Mpx 4K UHD Hikvision</a>	<a href="#">SWITCH POE GTX-A1-10-82- V2 8-PORT</a>	<a href="#">LED FLOODLIGHT AD- NL-6254BL4 ADVITI</a>
				
	222.86 HUF 222.86 HUF	231904.76 HUF 231904.76 HUF	20571.43 HUF 20571.43 HUF	3795.24 HUF 3795.24 HUF
Luminous flux	...	...	...	2400 lm
Standard	...	TCP/IP	...	...
Application	Power supply adapters of the RSP-200/320 and LRS-200/350 series	...	...	...
Sensor	...	1/1.8 " Progressive Scan CMOS	...	...
Material	Plastic, (transparent)	...	...	...
Light color	...	...	...	Neutral, 4000 K
Matrix size	...	8.3 Mpx	...	...
Twilight switch	...	...	...	—
Nominal power	...	...	...	30 W
LAN ports	...	...	• 8 x RJ45 10/100 Base-T ( 8 x PoE (802.3af/at) ), • 2 x RJ45 10/100 Base-T - Uplink	...
Power factor	...	...	...	0.8
Management	...	...	—	...
CRI	...	...	...	> 80
LED diodes	...	...	Power, S - Extend, PoE, Link/Act	...
Transmission speed	...	...	10 / 100 Mbps : 8 LAN & PoE ports + 2 Uplink ports	...
Resolution	...	3840 x 2160 - 8.3 Mpx 4K UHD , 3200 x 1800 - 6 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	...	...
Lens	...	4 mm	...	...
Main features	...	...	...	• LED SMD diodes • LED lifetime 30 000 h • Solid workmanship • IK rating : IK04
Maximal output power	...	...	30 W / port PoE 802.3af/at - 1 ... 8 ports	...
Maximal total power	...	...	96 W	...
View angle	...	• 90 ° (manufacturer data) • 85 ° (our tests result)	...	...
White light LED illuminator range	...	40 m	...	...
Range of IR illumination	...	40 m	...	...
Memory card slot	...	Micro SD memory cards up to 512GB support (possible local recording)	...	...
Operation modes	...	...	• N - Normal - the device operates as normal PoE switch • S - Extend - Range : 250 m @ 10 Mbps	...
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...	...
Alarm inputs / outputs	...	—	...	...
Certificates	...	...	CE	...
Audio	...	• Microphone built-in • Audio transmission via network • Compliance with the AAC standard • Noise and echo reduction	...	...
Main stream frame rate	...	25 fps @ 8.3 Mpx	...	...
Network interface	...	10/100 Base-T (RJ-45)	...	...
WEB Server	...	Built-in	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Max. number of on-line users	...	6	...	...
ONVIF	...	19.12	...	...
Operation temp	...	...	-10 °C ... 55 °C	-20 °C ... 50 °C
Main features	...	<ul style="list-style-type: none"> <li>• Smart Hybrid Light / ColorVu technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality</li> <li>• WDR - 130 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• Auto White Balance</li> <li>• AGC - Automatic Gain Control</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Mirror - Mirror image</li> <li>• Configurable Privacy Zones</li> <li>• Sharpness - sharper image outlines</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion, scene changing, detection of entry into the area / exit from the area, face detection</li> </ul>	...	...
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) • Android: Free application <a href="#">Hik-Connect</a> • iOS: Free application <a href="#">Hik-Connect</a>	...	...
Default IP address	...	192.168.1.64	...	...
Default admin user / password	...	admin / - The administrator password should be set at the first start	...	...
Web browser access ports	...	80	...	...
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...	...
Mobile client access ports	...	8000	...	...
Port ONVIF	...	80	...	...
RTSP URL	...	<ul style="list-style-type: none"> <li>• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/</li> <li>• Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/</li> </ul>	...	...
Power supply	...	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 580 mA</li> </ul>	100 ... 265 V AC	230 V AC
Power consumption	...	<ul style="list-style-type: none"> <li>• ≤ 8.5 W @ PoE</li> <li>• ≤ 7 W @ 12 V DC</li> </ul>	...	...
Housing	...	Compact, Metal	Desktop, Metal	Aluminum
Color	...	White	...	...
"Index of Protection"	...	IP67	...	IP65
Vandal-proof	...	—	...	...
Operation temp	...	-30 °C ... 60 °C	...	...
Weight	...	0.52 kg	0.66 kg	0.33 kg
Dimensions	89 x 10 x 4 mm	234 x 120 x 117 mm	207 x 105 x 32 mm	155 x 105 x 44 mm
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Vietnamese, Italian	...	...
Manufacturer / Brand	...	Hikvision	...	ORNO / ADVITI
SAP Code	...	311323640	...	...
Guarantee	2 years	3 years	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00