


	BATTERY AKU- AAA-950/GC*P4 1.2 V Ni-MH HR03, AAA Green Cell	IP MOBILE CAMERA DS-2XM6522G0-IM/ND - 1080p 2.8 mm Hikvision	FLUSH BOX P-80F SIMET
			
	40.59 DKK 40.59 DKK	2706.32 DKK 2706.32 DKK	11.20 DKK 11.20 DKK
Standard	...	TCP/IP	...
Sensor	...	1/2.8 " Progressive Scan CMOS	...
Number of sections	1
Scanning system	...	Progressive	...
Matrix size	...	2.1 Mpx	...
In package	4 pcs The price for package
Rated voltage	1.2 V
Battery capacity	950 mAh
Battery type	Ni-MH
Size	HR03, AAA
Main features	<ul style="list-style-type: none"> • Flush-mounted, for hollow walls • Cover mounting with screws • 4 Mounting screws, 2 special screws with holders to fastening to the wall - included
Resolution	...	1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p	...
Material	Plastic
Lens	...	2.8 mm	...
View angle	...	• 104 °	...
Mounting holes distance	75 mm
Compression	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Range of IR illumination	...	10 m	...
Alarm inputs / outputs	...	—	...
Audio	...	—	...
Memory card slot	...	—	...
Main stream frame rate	...	25 fps @ 1080p	...
Network interface	...	10/100 Base-TX The connection cable has been terminated with the M12 connector	...
Network protocols	...	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, IEEE 802.1x, QoS, IPv6, Bonjour	...
WEB Server	...	Built-in	...
Max. number of on-line users	...	20	...
ONVIF	...	✓	...
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) • Android: Free application iVMS-4500 or Hik-Connect • iOS (iPhone): Free application iVMS-4500 or Hik-Connect	...

Default admin user / password	...	admin / -	...
Default IP address	...	192.168.1.64	...
Web browser access ports	...	80	...
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Mobile client access ports	...	8000	...
Port ONVIF	...	80	...
RTSP URL	...	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization 	...
RS-485 interface	...	—	...
Main features	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • EIS - Electronic Image Stabilization • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • HLC - High Light Compensation (spot) • BLC - Back Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Configurable Privacy Zones • Lens focus loss detection • The device has a built-in heater • Intelligent image analysis : Motion Detection, intrusion, crossing the line (tripwire), detection of entry into the area / exit from the area, abandoned/missing object, scene changing, face detection 	...
Power supply	...	PoE (802.3af)	...
Power consumption	...	≤ 8.8 W	...
Housing	...	Compact, Aluminum	...
Color	...	Black	Orange / White
Vandal-proof	...	IK10	...
"Index of Protection"	...	IP68	IP30
Operation temp	...	-40 °C ... 70 °C	...
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Vietnamese, Italian	...
Weight	0.012 kg	0.88 kg	0.040 kg
Dimensions	...	164 x 123 x 65 mm	Ø 87 x 50 mm (flush mounting box) Ø 80 x 1 mm (cover)
Manufacturer / Brand	Green Cell	Hikvision	SIMET
SAP Code	...	311311921	...
Guarantee	2 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00