



	CCTV CABLE K-60+2X0.50/200	AHD, HD-CVI, HD-TVI, PAL CAMERA APTI-H24M-36 - 1080p 4 mm
		
	231.43 HUF 231.43 HUF	16000.00 HUF 16000.00 HUF
Standard	...	AHD / HD-CVI / HD-TVI / PAL
In section	200 m . Price for 1m when buying a whole roll	...
Coaxial cable	K-60	...
Sensor	...	1/2.8 " Sony CMOS - STARVIS Back-illuminated
Matrix size	...	2.1 Mpx
Dielectric	Ø 3.7 mm PE full	...
Shield	Al foil + PET	...
Braid	Wire Cu	...
Impedance	75 Ω	...
Outer coating	Ø 5.5 mm PVC	...
Cable attenuation at 100m section	10.6 dB @ 100 MHz 15.2 dB @ 200 MHz 25.4 dB @ 500 MHz 38.9 dB @ 1000 MHz	...
Resolution	...	<ul style="list-style-type: none"> • 1920 x 1080 - 1080p, AHD / HD-CVI / HD-TVI, • 1280 x 720 - 720p / AHD / HD-CVI / HD-TVI, • 960 x 576 - 960H, PAL
Lens	...	4 mm
Inner conductor	Ø 0.59 mm Cu - Wire 2 x 0.5 mm ² Stranded wire	...
View angle	...	<ul style="list-style-type: none"> • 72 ° (manufacturer data) • 80 ° (our tests result)
Power wires resistance	4 Ω / 100 m	...
Min. illumination	...	0.001 Lux
Video output	...	1 V _{pp} / 75 Ω - AHD / HD-CVI / HD-TVI / PAL
Audio	...	—

Main features	...	<ul style="list-style-type: none"> • WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC - configurable Back Light Compensation • White Balance - ATW/Manual • AGC - Automatic Gain Control • Sharpness - sharper image outlines • Day/Night mode (color/b&w/auto)
OSD menu	...	✓
Housing	...	Mini, Metal
Color	...	Black
Application	...	The camera is designed for indoor use, due to the possibility of steam condensation.
Power supply	...	12 V DC / 120 mA
Operation temp	...	-10 °C ... 50 °C
Weight	...	0.03 kg
Dimensions	...	30 x 30 x 29 mm (without bracket)
Supported languages	...	Polish, English, French, Spanish, Japanese, Portuguese, Russian, Italian
Manufacturer / Brand	...	APTI
Guarantee	2 years	2 years