




	DOORPHONE OR-DOM-RL-913	IP CAMERA APTI-AI504VA21-28W - 5 Mpx 2.8 mm	MOUNT RACK FRAME A19S-1U
			
	252.89 DKK 252.89 DKK	674.08 DKK 674.08 DKK	82.22 DKK 82.22 DKK
Standard	...	TCP/IP	...
Number of buttons (tenants)	1
Sensor	...	1/2.8 " SONY Starvis™ Back-illuminated CMOS	...
proximity reader built-in	—
Matrix size	...	5 Mpx	...
Mount	<ul style="list-style-type: none"> • Surface-mounted • Flush-mounted
Main features	<ul style="list-style-type: none"> • LED illuminator • Small dimensions
Resolution	...	2592 x 1944 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 720p	...
Communication	via cable (duplex)
Lens	...	2.8 mm	...
Length of the cable	0 ... 100 m (0.6 ... 0.8) mm ² (not included)
View angle	...	<ul style="list-style-type: none"> • 107 ° (manufacturer data) • 93 ° (our tests result) 	...
Range of IR illumination	...	30 m	...
Memory card slot	...	—	...
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	...	—	...
Audio	...	<ul style="list-style-type: none"> • External microphone input, • Audio output, • Bi-directional audio streaming support, • Compliance with the AAC standard 	...
Main stream frame rate	...	max. 25 fps @ 5 Mpx	...
Network interface	...	10/100 Base-T (RJ-45)	...
Network protocols	...	TCP/IP, IPv4/IPv6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, SNMP, SMTP, UDP, QoS, IEEE 802.1x	...
WEB Server	...	Built-in	...

Max. number of on-line users	...	10	...
ONVIF	...	19.12	...
Main features	Electric strike can be powered directly from uniphone	<ul style="list-style-type: none"> • Intelligent image analysis : intrusion, crossing the line (tripwire), loitering detection, detection of people gathering, vehicle detection • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • Flicker Control - The technology eliminates the tiring eyes flickering image effect • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • Motion Detection • Privacy zones - max. 3 • Mirror - Mirror image • Day/Night mode - configurable • Sharpness - sharper image outlines 	...
Mobile phones support	...	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BitVision • iOS (iPhone): Free application BitVision 	...
Default IP address	...	192.168.1.168	...
Default admin user / password	...	admin / admin	...
Web browser access ports	...	80	...
PC client access ports	...	80	...
Mobile client access ports	...	80	...
Port ONVIF	...	80	...
RTSP URL	...	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream	...
Power supply	230 V AC	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 700 mA 	...
Power consumption	< 2.7 W Standby < 5.5 W Operation	≤ 8.4 W	...
Housing	...	Dome, Metal	...
Color	Gray	White	Black
"Index of Protection"	...	IP67	...

Operation temp	...	-20 °C ... 60 °C	...
Weight	0.2 kg 0.55 kg	0.62 kg	0.53 kg
Dimensions	65 x 142 x 51 mm 99 x 216 x 65 mm	Ø 127 x 94 mm	490 x 102 x 55 mm - RACK 19", 1U
Supported languages	...	Polish, English, Bulgarian, Czech, French, Spanish, Dutch, German, Portuguese, Turkish, Italian	...
Manufacturer / Brand	ORNO	APTI	...
Guarantee	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00