





	AHD, HD-CVI, HD-TVI CVBS, TCP/IP DVR XVR5104HE-I3 4 CHANNELS DAHUA	BLANK PANEL TO RACK CABINET Z19-4U*P2	THERMOSTAT MOUNTING EAR A19-TT	PANEL WITH CABLE ENTRY A19-PK-V1
				
	334.06 CAD 334.06 CAD	16.05 CAD 16.05 CAD	2.25 CAD 2.25 CAD	8.00 CAD 8.00 CAD
In package	...	2 pcs The price for package
Standard	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP
Width	...	19 "	...	19 "
Video inputs	4 pcs BNC
Height	...	4 U	...	1 U
Application	Rack 19"	RACK 19"
Material	...	Steel - powder painted	Steel - powder painted	Steel - powder painted
Video outputs	1 pcs HDMI 1 pcs VGA
Main features	<ul style="list-style-type: none"> • Dimensions of the cable entry hole : 431 x 27 mm (full frame) • 4-point fixing to the front RACK rails • 4 pcs. of M6 screws with cage nuts included • Corrosion resistance
Audio inputs	4 pcs - CINCH 4 - Audio support via coaxial cable, HD-CVI only
Audio outputs	1 pcs CINCH
Image compression method	AI Coding / H.265+ / H.265 / H.264+ / H.264
Image records resolutions	AHD / HD-CVI / HD-TVI : 5M-N - 1296 x 1440 , 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720 , CVBS : 960H - 960 x 576 IP : max. 6 Mpx - 3072 x 2048

Recording speed adjustment	6 Mpx IP @ 1 ... 25 fps 5M-N @ 1 ... 10 fps 4M-N @ 1 ... 15 fps 1080p @ 1 ... 15 fps 1080N @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel
Operation modes	4 x AHD / HD-CVI / HD-TVI / CVBS / IP + 2 x IP
Recording modes	Manual, Sensor, Motion detection, Schedule
Supported hard drives	1 x 6 TB SATA
External storage devices backup	Save single frames and whole records from DVR drive to the USB drive
Searching and playback the records	Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy) Intelligent face search AI - simultaneous search in the archive of face recordings based on max 8 photos taking into account the similarity threshold (for each photo separately) 1/4 channel synchronous playback
Network functions	Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS See how to configure the P2P function in Dahua recorders and how to enable the mobile application
Alarm inputs / outputs	8 / 3
PTZ control	IP Speed Dome Cameras Control compatible with coax PTZ HD-CVI RS-485 - PELCO-D/P
Motion Detection	Split the screen into zones : 22 x 18 motion zones

Main features	<ul style="list-style-type: none"> • Cooperation with Dahua devices working in the concept of the Internet of Things (IoT), • POS - support the machines installed in the points of sales and displaying the date from them as overlaid text on selected channel window, • SMD PLUS - searching for an object classified as: human, motor vehicle • Coax Audio/Alarm support, • Intelligent image analysis : crossing the line (tripwire), intrusion, classification of people and vehicles • advanced face recognition and search functions • Support for up to 10 face databases, including 10 000 face images • Detection of faces not included in the device database • Searching for faces in recordings based on max 8 selected photos with the ability to independently set the similarity threshold for each photo
USB	2 pcs USB 2.0
Mouse support	✓
IR remote controller in the set	—
Power supply	12 V DC / 1.5 A (power adapter included)
Color	Black	Black	Black	Black (RAL 9005)
Weight	1.18 kg	0.9 kg	0.036 kg	0.25 kg
Dimensions	325 x 257 x 55 mm	...	97 x 68 x 1 mm	483 x 44 x 12 mm
Supported languages	Polish, English, Czech, Danish, Finnish, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Hungarian, Italian
Country of origin	China
Manufacturer / Brand	DAHUA
Guarantee	3 years	2 years	2 years	2 years