



	ACCESS POINT 4G LTE +ROUTER TL-MR6400 300Mb/s TP-LINK	ACCESS POINT 4G+ LTE Cat. 6 +ROUTER ARCHER-MR600 Wi-Fi 2.4 GHz, 5 GHz 867 Mbps + 300 Mbps TP-LINK
		
	76.25 EUR 76.25 EUR	148.64 EUR 148.64 EUR
Frequency range	2.4 GHz	2.4 GHz , 5 GHz
Antenna type	2 x WiFi built-in , 2 x 4G LTE - 2 x SMA socket - Possibility to connect the wire antenna	WiFi - built-in , 2 x 4G LTE
Standards	802.11n/g/b IEEE 802.3/3u	<ul style="list-style-type: none"> • IEEE 802.11 b/g/n, • IEEE 802.11 a/n/ac
Baud rates	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 150 Mbps	<ul style="list-style-type: none"> • 5 GHz : 867 Mbps (max) + 2.4 GHz : 300 Mbps (max) • LTE : 300 Mbps
Modulation type	DBPSK, DQPSK, CCK OFDM, 16-QAM, 64-QAM	...
LAN ports	<ul style="list-style-type: none"> • 1 x 10/100 Mbps - LAN/WAN • 3 x 10/100 Mbps - LAN 	<ul style="list-style-type: none"> • 1 x 10/100/1000 Mbps - LAN/WAN • 3 x 10/100/1000 Mbps - LAN
Receiver sensitivity	<ul style="list-style-type: none"> • 11g 54M: -74dBm • 11n HT20: -71dBm • 11n HT40: -67dBm 	5 GHz : <ul style="list-style-type: none"> • 11a 54M: -74dBm • 11ac HT20: -66 dBm • 11ac HT40: -63 dBm • 11ac HT80 : -59 dBm • 11n HT20: -73dBm • 11n HT40: -70dBm 2.4 GHz : <ul style="list-style-type: none"> • 11g 54M: -74dBm • 11n HT20: -72 dBm • 11n HT40: -69 dBm
LTE	✓	✓
QSS	✓	—
WDS	✓	✓
Transmitter power	...	max. 23 dBm

Main features	<ul style="list-style-type: none"> • SIM socket • WPS/RESET button 	<ul style="list-style-type: none"> • IP-layer bandwidth control mechanism • Local, remote or via TP-Link Cloud management • Support for TP-Link OneMesh™ technology • SIM socket • WPS/RESET button
Power supply	9 V DC / 1 A (power adapter included)	12 V DC / 1.5 A (power adapter included)
Operation temp	0 °C ... 40 °C	0 °C ... 40 °C
Permissible relative humidity	max. 95 % (non-condensing)	95 % (non-condensing)
Weight	0.354 kg	0.478 kg
Dimensions	202 x 141 x 34 mm	230 x 163 x 37 mm
Manufacturer / Brand	TP-LINK	TP-LINK
Guarantee	3 years	3 years