



	<a href="#">IP CAMERA APTI-54C2-28WP - 5 Mpx 2.8 mm</a>	<a href="#">PORTABLE POWER STATION TRAVEL-POWERBOX-OPTI-1200 461 Wh 600 W VOLT Polska</a>
		
	104.64 CAD 104.64 CAD	464.48 CAD 464.48 CAD
Standard	TCP/IP	...
Sensor	1/2.8 " SONY Starvis™ Back-illuminated CMOS	...
Digital Image Processor	Hisilicon 3516D	...
Matrix size	5.1 Mpx	...
Battery capacity	...	461 Wh ( 20.8 Ah / 22.2 V )
Maximal load power	...	600 W
Number of inputs	...	1 pcs
Number of outputs	...	9 pcs
Power inputs	...	1 pcs 5.5/2.1 socket, 12 ... 24 V DC / 5.5 A (battery charging)
Resolution	2592 x 1944 - 5 Mpx , 2592 x 1536 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Lens	2.8 mm	...
View angle	• 93 ° (manufacturer data) • 96 ° (our tests result)	...
S/N ratio	≥ 52 dB	...
Range of IR illumination	30 m	...
IR illuminator power adjustment	Automatic	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Main stream frame rate	20 fps @ 5 Mpx 25 fps @ 4 Mpx	...
Network interface	10/100 Base-T (RJ-45)	...
Memory card slot	Micro SD memory cards up to 128GB support (possible local recording)	...
Alarm inputs / outputs	—	...
Audio	—	...
Network protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP	...

Power outputs	...	<ul style="list-style-type: none"> <li>• 2 pcs AC - Power socket, CEE 7/3 (Schuko), 2 x 230 V / 50 Hz (Pure Sine Wave),</li> <li>• 3 pcs DC1 - 5.5/2.1 socket, 3 x 12 V / 3 A,</li> <li>• 1 pcs DC2 - Car cigarette lighter socket, 12 V / 10 A,</li> <li>• 1 pcs USB-C, PD3.0 max. 60 W ( 5, 9, 12, 15, 20 V / 3 A Auto ),</li> <li>• 2 pcs USB-A, Quick Charge 3.0 max. 18 W ( 2 x 5 V / 3 A, 9 V / 2 A, 12 V / 1.5 A )</li> </ul>
WEB Server	Built-in - port 80	...
Max. number of on-line users	10	...
ONVIF	2.4	...
RS-485 interface	—	...
Protections	...	<ul style="list-style-type: none"> <li>• Short-circuit</li> <li>• Overload</li> <li>• Overvoltage</li> <li>• Discharge</li> <li>• Temperature</li> </ul>
Mobile phones support	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">BitVision</a></li> <li>• iOS (iPhone): Free application <a href="#">BitVision</a></li> </ul>	...
Default admin user / password	admin / admin	...
Default IP address	192.168.1.168	...
Web browser access ports	80	...
PC client access ports	80	...
Mobile client access ports	80	...
Port ONVIF	80	...
RTSP URL	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream	...
Main features	...	<ul style="list-style-type: none"> <li>• Li-Ion battery</li> <li>• Large, readable LCD display with backlight</li> <li>• One-touch action buttons</li> <li>• White light (LED) illuminator built-in 2 W - lighting brightness control ( 3 levels ) + SOS</li> <li>• Fan cooler built-in</li> <li>• Battery charging ≥ 800 cycles</li> <li>• Automatic power-off</li> </ul>

Main features	<ul style="list-style-type: none"> <li>• 2D-DNR</li> <li>• ICR - Movable InfraRed filter</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• Flicker Control - The technology eliminates the tiring eyes flickering image effect</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• BLC - Back Light Compensation</li> <li>• Motion Detection</li> <li>• Privacy zones</li> <li>• Mirror - Mirror image</li> <li>• Day/Night mode - configurable</li> </ul>	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 450 mA</li> </ul>	<ul style="list-style-type: none"> <li>• 19 V DC / 4.73 A (power adapter included)</li> <li>• 12 ... 24 V DC / 5.5 A - Car lighter plug (cable included)</li> <li>• 13 ... 24 V DC - Solar Panel</li> <li>60 ... 100 W (cable included)</li> </ul>
Charging time (recover to 100% capacity)	...	5 ... 7 h
Power consumption	≤ 5.4 W	...
Operation temp	...	0 °C ... 40 °C
Housing	Compact, Aluminum	...
Color	White	...
"Index of Protection"	IP66	...
Operation temp	-20 °C ... 60 °C	...
Weight	0.35 kg	4.94 kg
Dimensions	Ø 73 x 151 mm	290 x 164 x 235 mm
Supported languages	Polish, English, Bulgarian, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian	...
Manufacturer / Brand	APTI	VOLT Polska
Guarantee	2 years	2 years