



	SWITCH POE HS4408-4ET-96 4-PORT + 4 x SFP DAHUA	ROUTER ER-X EdgeMAX UBIQUITI
		
	116.28 EUR 116.28 EUR	65.47 EUR 65.47 EUR
Standards	...	IEEE 802.3ad, IEEE 802.1q
Processor	...	Dual-Core 880 MHz, MIPS1004Kc
WAN interface	...	configurable
LED indicators	...	Power, LAN
DDNS	...	✓
DHCP server	...	✓
LAN ports	<ul style="list-style-type: none"> • 4 x RJ45 (10/100/1000 Base-T, 3 PoE (802.3af/at) + 1 PoE (802.3bt) / Hi-PoE / PoE (802.3af/at)) • 4 x Uplink (port SFP - 1000 Base-X) 	5 x LAN 10/100/1000 Mbps (RJ-45)
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 LAN & PoE ports • 1000 SFP ports 	...
Protections	...	<ul style="list-style-type: none"> • NAT network firewall • LAN ACL • Contact/Air (ESD/EMP) : ± 24 kV / ± 24 kV
Management	✓	...
Management interface	...	<ul style="list-style-type: none"> • Software EdgeOS, Software PC • Remote management • Web browser
Maximal output power	<ul style="list-style-type: none"> • 30 W / port PoE 802.3af/at • 90 W / port PoE 802.3bt 	...
Maximal total power	96 W	...
Operation modes	<ul style="list-style-type: none"> • Extend On : 250 m, 10 Mbps • Extend Off : 100 m, 10 / 100 Mbps 	...
Power supply PoE	...	Ubiquiti Passive PoE

Main features	<ul style="list-style-type: none"> • DIN, TS-35 rail mounting • Data Flow Control • protection against lightning discharges and voltage differences and strokes between devices • Industrial wide temperature design. • Intelligent management of Power Supply Unit power's output stage • PoE (802.3af), PoE (802.3at), Hi-PoE, PoE (802.3bt) • PoE Watchdog / PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • The ability to connect two power adapters - redundant power supply • The device supports 8-pin power supply 	<ul style="list-style-type: none"> • IEEE 802.1Q VLAN • PPPoE • Static routing • DHCP • IPv6 compliance • IGMP • NAT • VPN networks: IPsec VPN, L2TP VPN, PPTP VPN, Open VPN • Dynamic DNS • Client - Radius support • QoS - mechanisms, which provide the high quality of transmission • Switch is managed via a web browser, command line interface and SNMP, NetFlow, LLDP, NTP, UBNT Discovery Protocol protocols • View topology and network status • RESET button • Possible power supply via Passive PoE via eth4/Poe OUT port - 24 V ("+" : 4, 5 pins; "-" : 7, 8 pins) • Possibility to mount to the wall
LED diodes	Power, Link/Act, PoE	...
Power consumption	...	max. 5 W
Housing	...	Metal
Certificates	CE	...
Power supply	48 ... 57 V DC (power adapter included)	<ul style="list-style-type: none"> • 12 V DC / 0.5 A (power adapter included) • Passive PoE 24 V - port eth0/PoE IN
Permissible relative humidity	...	10 % ... 90 % (non-condensing)
Housing type	DIN	...
Operation temp	-30 °C ... 65 °C	-10 °C ... 45 °C
Weight	0.618 kg	0.172 kg
Dimensions	150 x 110 x 42 mm	110 x 75 x 22 mm
Manufacturer / Brand	DAHUA	UBIQUITI
Guarantee	3 years	2 years